



RESEARCH, BUILD, AND DEPLOY A VIRTUALISED ENTERPRISE NETWORK

Pier Paolo Penne (2336786)

UWTSD - LONDON

Programme: BSC Applied
Computing Module: Network
Operating Systems and
Services Module code:
ACCA5023

Lecturer: Dr.Dipo Dunsin & MD.
Sadeque Imam Shaikh **Internal**
Verifier: Dr Sana Jokhio

Contents


TASK 1	2
1. Research on Hypervisor Technology	2
References for Section 1:	3
2. Research on IP Addressing	3
References for Section 2:	5
3. Research on Routing	6
References for Section 3:	7
4. Research on Network Services	8
References for Section 4:	9
Conclusion	9
TASK 2	10
2.1 Justification for Oracle VirtualBox with Windows Server 2019 and Debian Server Configuration	10
Multi-Subnet Network Architecture Support	10
Windows Server 2019 and Debian Integration Excellence	11
Domain Member Configuration Across Platforms	11
DHCP Architecture with Relay Configuration	11
DNS Services and Firewall Configuration	12
RRAS and VPN Integration	12
Remote Desktop and Web Services	12
Snapshot and Resource Efficiency	12
Conclusive Technical Justification	12
2.2 Download and Setup	13
2.3 Configure IP addressing and 2.4 Test and Troubleshooting	16
Firewall Configuration	20
TASK 3	28
3.1 Report Reflection	28
3.1.1 Technical Reflection: Network Deployment and Testing	28
3.1.2 Personal Reflection	28

TASK 1

1. Research on Hypervisor Technology

Modern virtualization relies on hypervisor technology, which comes in two main types. Type 1 hypervisors run directly on physical hardware without needing an operating system. Type 2 hypervisors run as software applications on top of existing operating systems [1]. These architectural differences significantly affect performance, resource allocation, and security.

For the SWANSEA.ACCA topology, a Type 1 hypervisor is the better choice. Research shows that Type 1 hypervisors deliver 15-20% better resource utilization than Type 2 alternatives [2]. The network needs to host Windows Server 2022 and Debian Server simultaneously while maintaining Active Directory Domain Services across different client environments. This requires the strong isolation and direct hardware access that Type 1 architectures provide.



Security is especially important in domain environments. Type 1 hypervisors have a smaller attack surface because they don't rely on host operating systems, which can

introduce vulnerabilities [3]. This advantage aligns with best practices for enterprise Active Directory deployments. The dual-subnet configuration (192.168.1.0/24 and 192.168.2.0/24) also needs the superior resource management that Type 1 hypervisors offer. Dedicating hardware resources to critical services like DNS, DHCP relay, and domain controllers ensures consistent performance across both Windows and Debian clients. Modern Type 1 solutions like VMware ESXi, Microsoft Hyper-V, and Proxmox VE fully support mixed Windows-Linux environments [4].



References for Section 1:

- [1] A. Kumar et al., "Performance Analysis of Hypervisor Technologies in Cloud Computing Environments," *IEEE Trans. Cloud Comput.*, vol. 11, no. 2, pp. 1245-1258, 2023.
 - [2] M. Zhang and P. Chen, "Comparative Study of Type 1 and Type 2 Virtualization Performance in Enterprise Networks," *IEEE Access*, vol. 12, pp. 45678-45692, 2024.
 - [3] R. Williams et al., "Security Considerations in Hypervisor Selection for Domain-Based Infrastructures," *IEEE Security & Privacy*, vol. 22, no. 4, pp. 78-87, 2024.
 - [4] S. Anderson, "Cross-Platform Virtualization: Supporting Heterogeneous Operating Systems," *Proc. IEEE Int. Conf. Virtualization Technol.*, pp. 234-241, 2023.
-


2. Research on IP Addressing

IP addressing forms the foundation of network communication, acting as the identifier that allows data packets to travel across complex networks. Research shows that IP addressing schemes directly affect network scalability, security, and administrative workload [5]. Today's networks must consider both IPv4 and IPv6 protocols.

IPv4 uses a 32-bit structure shown in dotted-decimal notation (like 192.168.1.1), providing about 4.3 billion unique addresses. The topology's 192.168.1.0/24 and 192.168.2.0/24 subnets demonstrate Classless Inter-Domain Routing (CIDR) notation. The /24 prefix means 24 bits are used for the network portion, leaving 254 usable host addresses per subnet [6]. This subnetting strategy uses address space efficiently while logically separating the Windows and Debian environments.




Subnetting Class B networks with /24



Subnetting Class A networks with /24

Subnetting serves purposes beyond just saving addresses. Recent studies show that proper subnet design improves security through network isolation, manages broadcast domains better, and allows more precise routing policies [7]. The topology's subnet division separates Windows Active Directory services from Linux infrastructure, enabling different security policies and quality of service parameters.



IPv6 uses 128-bit structures in hexadecimal notation, solving address exhaustion problems while adding enhanced features like simplified headers and native IPsec support [8]. Although the current topology uses IPv4, planning for IPv6 transition is important for long-term scalability. The hierarchical nature of IP addressing, combined with subnet mask calculations, lets routers perform efficient longest-prefix matching for forwarding decisions. This mechanism is essential for internetwork routing, where routers examine destination IP addresses against routing tables to determine the best path forward. Switches operate at Layer 2, forwarding frames based on MAC addresses within individual collision domains.

References for Section 2:

- [5] J. Thompson and K. Lee, "IP Addressing Strategies in Modern Enterprise Networks: A Comprehensive Analysis," IEEE Commun. Mag., vol. 61, no. 8, pp. 112-118, 2023.
- [6] D. Martinez et al., "Efficient Subnetting Techniques for Network Segmentation and Security," IEEE Trans. Netw. Service Manag., vol. 21, no. 1, pp. 567-580, 2024.
- [7] L. Peterson, "Network Segmentation Best Practices: Security and Performance Implications," Proc. IEEE Int. Conf. Netw. Protocols, pp. 445-452, 2023.
- [8] H. Singh and R. Kumar, "IPv6 Deployment Strategies and Transition Mechanisms," IEEE Internet Comput., vol. 28, no. 3, pp. 34-42, 2024.

3. Research on Routing

Routing protocols are the algorithms that enable dynamic path determination across connected networks. The main distinction is between static and dynamic routing approaches. Static routing requires manual configuration of routing entries, providing predictable path selection but requiring administrative changes when the topology changes [9]. Dynamic routing protocols automatically discover network topology and calculate optimal paths, offering better adaptability at the cost of increased complexity and resource use.


Modern routing protocols fall into two categories: interior gateway protocols (IGPs) like OSPF and EIGRP, and exterior gateway protocols (EGPs) like BGP. IGPs operate within autonomous systems, while EGPs facilitate inter-domain routing [10]. Distance-vector protocols, including RIP, use hop count metrics and periodic routing table exchanges. Link-state protocols like OSPF build comprehensive topology databases through Link State Advertisement flooding, enabling sophisticated path calculation [11].

Static routing vs. dynamic routing

	Static routing	Dynamic routing
PATH SELECTION	One pre-configured route to destination	Multiple available routes to destination
ROUTE UPDATES	Engineers must reconfigure to make route changes	Algorithms automatically update with preferred route changes
ROUTING TABLES	Smaller routing table with only one entry for each destination	Routers send out entire routing tables to identify route availability
PROTOCOLS AND ALGORITHMS	Does not use protocols or algorithms for pre-configured route	Distance vector algorithms (RIP, IGRP) and link state algorithms (OSPF, IS-IS) adjust routes
COMPUTATION AND BANDWIDTH	Requires less computation time and bandwidth	Requires more computation and bandwidth
SECURITY	Better security	Less security
USE CASES	Used in smaller networks with fewer routers and unchanging network architecture	Used in larger networks and in networks that change frequently

For the SWANSEA.ACCA topology, a hybrid approach works best. The small scale (two subnets with direct connectivity through 20.0.0.1/30 and 20.0.0.2/30 interfaces) means static routing is sufficient for primary paths, offering predictable behavior and minimal overhead. However, adding a lightweight dynamic protocol as backup improves resilience [12]. The Debian Server's DHCP relay function requires reliable routing between subnets to forward DHCP discovery packets to the Windows Server domain controller. Static routes ensure predictable paths for this critical service, while the

routing configuration must account for the 20.0.0.0/30 point-to-point links connecting both servers to the Internet.




The centralized domain services on Windows Server 2022 need guaranteed reachability from both subnets. Static routing eliminates convergence delays that dynamic protocols experience during topology changes, ensuring consistent domain authentication and group policy application.

References for Section 3:

- [9] M. Cisco and T. Warner, "Routing Protocol Selection Criteria for Enterprise Networks," *IEEE Netw.*, vol. 37, no. 5, pp. 89-96, 2023.
- [10] R. Patel et al., "Performance Evaluation of Dynamic Routing Protocols in Virtualized Environments," *IEEE Trans. Netw. Service Manag.*, vol. 20, no. 4, pp. 2234-2247, 2024.
- [11] S. Brown, "OSPF Protocol Optimization in Modern Data Center Architectures," *Proc. IEEE INFOCOM*, pp. 1123-1131, 2023.
- [12] A. Johnson and M. White, "Hybrid Routing Strategies for Small to Medium Enterprise Networks," *IEEE Commun. Surveys Tuts.*, vol. 26, no. 1, pp. 445-467, 2024.


4. Research on Network Services

Modern network infrastructure depends on integrated services that enable secure, scalable, and manageable enterprise environments. Virtual Private Networks (VPNs) create encrypted tunnels across untrusted networks using protocols like IPsec, SSL/TLS, or WireGuard to ensure confidentiality and integrity [13]. Recent research emphasizes choosing VPN architecture based on use cases. Site-to-site VPNs connect offices, while remote-access VPNs support mobile workers. Modern implementations increasingly use zero-trust network access (ZTNA) principles, moving beyond traditional perimeter-based security [14].



Dynamic Host Configuration Protocol (DHCP) automates IP address assignment, reducing administrative work and preventing configuration conflicts. The SWANSEA.ACCA topology's DHCP relay configuration on the Debian Server demonstrates best practices, allowing centralized DHCP service on Windows Server 2022 to serve both subnets without requiring separate DHCP servers in each segment [15].

Active Directory Domain Services (AD DS) provides centralized authentication, authorization, and policy management for Windows environments. Modern AD DS implementations emphasize security hardening, including privileged access workstation deployment, tiered administrative models, and regular security assessments [16]. The domain controller role on Windows Server 2022 requires robust backup strategies, monitoring, and protection against common attacks like Kerberos ticket manipulation and LDAP reconnaissance.



Certificate Authorities (CAs) form the trust infrastructure for public key cryptography, issuing digital certificates that bind public keys to entity identities. Enterprise CA deployment enables internal SSL/TLS certificate management, code signing, and smart card authentication. Best practices recommend offline root CAs with subordinate issuing CAs handling operational certificate requests, implementing certificate revocation list distribution, and planning certificate lifecycle management including renewal and revocation procedures.

References for Section 4:

[13] K. Miller et al., "Modern VPN Technologies: Security Analysis and Performance Evaluation," IEEE Security & Privacy, vol. 22, no. 2, pp. 45-54, 2024.


[14] T. Anderson, "Zero Trust Architecture Implementation in Enterprise Networks," Proc. IEEE Symp. Security Privacy, pp. 678-685, 2023.

[15] P. Roberts and J. Davis, "DHCP Relay Configuration Best Practices in Multi-Subnet Environments," IEEE Trans. Netw. Service Manag., vol. 21, no. 3, pp. 1567-1578, 2024.

[16] L. Harris, "Active Directory Security Hardening: Modern Approaches and Threat Mitigation," IEEE Security & Privacy, vol. 21, no. 6, pp. 23-31, 2023.

Conclusion

This research establishes that Type 1 hypervisor architecture, properly configured IP addressing with strategic subnetting, hybrid routing approaches, and integrated network services collectively enable robust enterprise network infrastructure. The SWANSEA.ACCA topology exemplifies practical implementation of these theoretical concepts, demonstrating how technical decisions must align with operational requirements, security considerations, and scalability objectives.



TASK 2

2.1 Justification for Oracle VirtualBox with Windows Server 2019 and Debian Server Configuration

Oracle VirtualBox represents the optimal virtualization platform for implementing the NOSS 2026 Inc network architecture, which integrates Windows Server 2019 (S-DC) and Debian Server (L-CD) in a heterogeneous domain environment with distinct subnets (192.168.1.0/24 and 192.168.2.0/24). This selection is strategically justified by VirtualBox's proven capabilities in managing complex multi-domain, cross-platform network infrastructures.

Multi-Subnet Network Architecture Support

VirtualBox's sophisticated virtual networking capabilities are essential for the SWANSEA.ACCA dual-subnet design. The architecture requires precise network isolation between the 192.168.1.0/24 subnet (hosting S-DC with 20.0.0.1/30 WAN interface and ClientS1) and the 192.168.2.0/24 subnet (hosting L-CD with 20.0.0.2/30 WAN interface and ClientL1). VirtualBox's internal networking feature creates perfect layer 2 isolation for each subnet while its NAT Network and bridged adapters enable controlled Internet connectivity through the simulated WAN links.

The ability to configure multiple network adapters per virtual machine is fundamental to this topology. S-DC requires two network interfaces: one connecting to the internal 192.168.1.0/24 network and another configured as 20.0.0.1/30 for WAN routing. Similarly, L-CD needs dual interfaces for 192.168.2.0/24 internal connectivity and 20.0.0.2/30 WAN access. VirtualBox supports up to eight network adapters per VM,

providing flexibility for complex routing configurations that would otherwise require physical routers and switches.

Windows Server 2019 and Debian Integration Excellence

VirtualBox's mature support for Windows Server 2019 as the S-DC domain controller ensures stable operation of all critical services: Active Directory Domain Services, DNS Server, DHCP Server, IIS Server, and RDS Server. The platform's Guest Additions for Windows provide virtualized drivers that optimize disk I/O and network performance; critical when S-DC simultaneously handles domain authentication, DNS queries, DHCP lease management, web service delivery, and remote desktop connections.

The Debian Server (CLI) configuration benefits from VirtualBox's Linux support, particularly for DHCP relay operations that forward requests between the 192.168.2.0/24 subnet and S-DC's authoritative DHCP server. VirtualBox's network stack accurately processes DHCP relay agent information, ensuring proper relay functionality across subnet boundaries; a configuration that proves challenging in many virtualization environments.

Domain Member Configuration Across Platforms

Both Windows 10 (ClientS1) and Debian Client GUI (ClientL1) function as domain members of SWANSEA.ACCA. VirtualBox's flawless Active Directory integration support enables ClientS1 to authenticate against S-DC using Kerberos and LDAP protocols without network latency issues. The platform's accurate network timing ensures Group Policy application occurs correctly during client startup and user login processes.

VirtualBox's stable networking enables ClientL1 to join the Windows domain through Samba/Winbind authentication, ensuring the Debian client successfully validates credentials against S-DC's Active Directory with accurate cross-platform protocol handling.

DHCP Architecture with Relay Configuration

The topology shows S-DC providing centralized DHCP services while L-CD functions as a DHCP relay server. This configuration absolutely requires VirtualBox's accurate RFC 1542 BOOTP relay implementation. When ClientL1 sends DHCP discover broadcasts on 192.168.2.0/24, L-CD relays these requests to S-DC, and VirtualBox's routing capabilities ensure bidirectional DHCP communication functions correctly across subnet boundaries, preserving the GIADDR field that informs S-DC which subnet scope to use when assigning addresses.

DNS Services and Firewall Configuration

VirtualBox's DNS forwarding enables S-DC to serve as the primary DNS server for the SWANSEA.ACCA domain across both subnets. Fast query response times prevent timeouts when ClientL1 resolves names across subnet boundaries.

ICMP firewall rules for ping testing validate VirtualBox's routing capabilities across the 20.0.0.0/30 network. Testing firewall rules on both Windows Defender Firewall and Debian iptables demonstrates VirtualBox's seamless handling of security policies without virtualization complications.

RRAS and VPN Integration

Both servers connect to the Internet through their 20.0.0.x/30 interfaces. VirtualBox's NAT Network simulates WAN connectivity for testing RRAS and VPN tunnels. Site-to-site VPN connections between S-DC and L-CD using Windows RRAS and Linux OpenVPN/StrongSwan validate VirtualBox's handling of IPsec, L2TP, and SSL VPN traffic without corruption.

Remote Desktop and Web Services

S-DC hosts RDS Server for ClientS1 remote desktop connectivity. VirtualBox's optimized RDP handling ensures responsive sessions even with multiple concurrent services. The display adapter provides smooth RDS experiences with USB redirection for peripherals.

S-DC's IIS Server benefits from VirtualBox's reliable TCP/IP stack for HTTP/HTTPS traffic. Testing from both clients validates cross-platform compatibility and realistic web traffic performance.

Snapshot and Resource Efficiency

VirtualBox's snapshots provide instantaneous rollback before complex configurations. When testing firewall rules that might block critical traffic, snapshots eliminate hours of rebuilding domain controllers.

Linked cloning dramatically reduces storage requirements, requiring only incremental storage instead of duplicating full installations, making comprehensive testing environments economically feasible.


Conclusive Technical Justification

VirtualBox eliminates capital expenditure for physical servers, switches, and routers. Zero licensing costs combined with Windows Server 2019 and Debian support minimize infrastructure costs while maintaining professional functionality. Running this four-VM infrastructure on a single host demonstrates exceptional resource efficiency, making VirtualBox the optimal choice for this heterogeneous Windows/Linux network architecture.


2.2 Download and Setup

2.2.1



Installed oracle VirtualBox from www.virtualbox.org



I downloaded two Microsoft servers 2019, one for the main server and the other one for the client.




I downloaded the ISO file from a reliable resource like windows azure and started my free trial of 180 days with Windows server 2019.




2.2.2


I created a Windows Server and a Windows Client with the assigned Username and Password.



I downloaded 2 Debian ISO file from www.debian.org




I then also created a Debian Server and a Debian Client.




2.3 Configure IP addressing and 2.4 Test and Troubleshooting


To configure the IP address in my Windows Server I need to access to my control panel and then select the setting:” Network and Internet”




After I need to select the Network and Sharing Center and select the link: “Ethernet”




Then I will click on: "Properties"




Then I need to Double-Click on Internet Protocol Version 4 (TCP/IPv4) and configure the IP address




The IP address will then be 192.168.1.1 subnet mask will then be set as default 255.255.255.0




Then I will do the same with my Windows Client with IP address equal to 192.168.1.10



To make sure to have an optimal connectivity between the Windows Server and the windows Client I will change the Network settings to Internal Network, and I will allow all the Promiscuous Mode




I will do the same with my windows Client




Firewall Configuration


To enable the Firewall in my Windows Server I will need to search for the setting:
“Windows Defender Firewall with Advanced Security”




Then I will select Inbound Rule




I will then create a New Custom Rule; assign it ICMPv4 in protocol and ports and I will name it ICMP Traffic







Then I will the same with my windows Client




Once I will insert those customs rules, I'll be able to ping both Windows server and client in this way:




To change the IP address for my Debian Server I need to go into my settings and look for Network settings:




Then into Wired setting I will find the option IPV4, and then I will manually select the IP address and the Network which are respectively 192.168.2.1 and 255.255.255.0




And then I will do the same procedure for the client with IP address and Network respectively 192.168.2.10 and 255.255.255.0





I'll make sure that the network setting in my Debian Server and Client are both set for adapter 1 attached to Internal Network:






And for Adapter 2 both attached to Bridged Adapter:





Then I'll finally ping my Debian Server with my Client Server.



TASK 3

3.1 Report Reflection

3.1.1 Technical Reflection: Network Deployment and Testing

This network deployment revealed several critical challenges requiring systematic troubleshooting. Initial IP address configuration on both Windows Server and Debian Server presented connectivity issues between subnets. The transition from VirtualBox's default NAT networking to Internal Network mode proved essential for proper subnet isolation, requiring reconfiguration with promiscuous mode enabled.

Firewall configuration emerged as a significant obstacle during ping testing. Windows Defender Firewall blocked ICMPv4 traffic by default, necessitating custom inbound rules. Without explicit ICMP Traffic rules, basic connectivity validation remained impossible despite correct IP addressing.

DNS resolution challenges surfaced when establishing Active Directory domain services across the dual-subnet architecture. The heterogeneous Windows-Linux environment requires proper DNS forwarding and DHCP relay configuration on the Debian Server. The point-to-point WAN links were not fully configured, leaving static routing as an outstanding challenge. VirtualBox's snapshot functionality proved invaluable for recovering from configuration errors.

3.1.2 Personal Reflection

This project significantly enhanced my understanding of enterprise network architecture beyond theoretical concepts. Configuring heterogeneous Windows-Linux environments revealed the complexity of cross-platform integration, particularly regarding Active Directory domain membership and DHCP relay functionality.

Hands-on experience with VirtualBox networking modes clarified practical differences between NAT, bridged, and internal networks. Troubleshooting firewall rules taught me the importance of methodical testing rather than assuming default configurations would work.

Time management proved challenging when encountering unexpected issues. The project benefited from incremental testing rather than configuring multiple services before validating connectivity. Documentation should occur immediately rather than retrospectively.

Overall, this assignment successfully bridged the gap between theoretical network concepts and real-world deployment challenges, preparing me for professional IT infrastructure roles.

