

University of Wales Trinity Saint David

Wales Institute of Science & Art



Adjustable Chassis Flex Systems

Academic and Laboratory Skills

(ACHA4032)

Ned Henderson

2506337

November 2025

1 Contents

1	Contents	i
2	Introduction	ii
3	Background	iii
4	Discussion	iv
4.1	Directional Stiffness	iv
4.2	Design Constraints	iv
4.3	Current Adjustable Solutions	v
5	Conclusion	vii
6	References.....	viii

2 Introduction

Production motorcycle chassis design presents a fundamental compromise of performance requirements. Sport touring and dual sport or adventure motorcycles prioritize stability and rider comfort for long distance riding, whilst sportbikes stress sharp handling and cornering precision. This report investigates whether introducing greater control for end users over chassis characteristics, specifically adjustable rigidity and flexibility, could enable a motorcycle to effectively serve both purposes better than current designs. The following analyses published research on chassis rigidity effects, examines adjustable geometry systems and racing-derived innovations to determine whether increased end-user adjustability represents a realistic solution for improved dual-purpose motorcycles.

3 Background

Earlier frames pursued maximum stiffness to eliminate handling instabilities, with engineers targeting ever-higher torsional stiffness values. Sharp (2001) identified three fundamental instability modes affecting motorcycle handling: capsize, the bike wanting to overturn; weave, involving side-to-side oscillation of the entire vehicle; and wobble, the side to side shaking of front wheel and handlebars. Understanding and controlling these modes drove chassis development priorities for decades.

Lake et al. (2012) explained that flexible frames promoted wobble problems at medium speeds, whilst extremely stiff frames transferred this instability to higher speeds. This led to increasingly rigid structures that pushed weave and wobble out of the normal operating range of the average road motorcycle, suggesting that maximizing stiffness represented the best all-round design.

However, challenges remain. Recent research by Sakai (2024) identified that caster angle has narrow "sweet spots" where self-excited oscillations do not occur, making it the most crucial variable in chassis design alongside trail and front wheel characteristics. The gap between the elements can be measured and what riders feel needs more research (Gadola et al., 2019). Testing methods linking chassis adjustments to rider feedback are needed, along with safety validation across different settings and road conditions.

Technology exists from racing and early production examples, but practical implementation needs better understanding of rider perception combined with mechanical design. Making chassis stiffness and geometry adjustable for end users could solve dual-purpose motorcycle needs, though whether these systems become mainstream or remain specialist features depends on understanding how riders use these adjustments.

4 Discussion

4.1 Directional Stiffness

From the research, it appears that motorcycle frames need different amounts of stiffness depending on which direction forces are acting. Kawata (2015) explained that during high-speed riding, braking forces applied to the frame are much larger than acceleration forces. To counteract this, the frame needs to be very stiff forwards-backwards to control braking stresses without bending too much. However, they found through Suzuki's racing testing that frames which were very stiff forward-backward but less so side-to-side cornered better than bikes that were stiff in both directions equally. This finding contradicted the previous view that a very rigid frame is the default ideal for a racing chassis.

Designing around this directional difference proved difficult with typical frame designs. Lake et al. (2012) note that the space between the steering head and engine is usually filled with the air intake system, restricting the ease of adding additional bracing tubes. Cameron (2018) explained that Japanese manufacturers typically bolted the steering head directly to the cylinder head underneath it, making the connection stiff in all directions, whilst Ducati's horizontal front cylinder meant this direct connection was impossible, creating the beneficial side-to-side flex.

Lake et al. (2012) found that allowing the swingarm to bend slightly can help stability at high speeds, but torsional twist has the opposite effect and makes handling worse. This shows that even within one component, different types of flexibility have varying effects on how the bike handles.

4.2 Design Constraints

The main problem described in the research is that changing stiffness in one direction usually affects the other directions too. Lake et al. (2012) showed that most motorcycle frames have a similar relationship between how stiff they are forwards-backwards compared to side-to-side. This link made it tough to use what racing had learned about directional stiffness on production motorcycles.

From Palanivendhan et al. (2020) paper, trellis frames are lightweight and very stiff which helps with straight-line speed, whilst perimeter frames are more compact and have some controlled flex which helps with high-speed cornering. But trying to get the benefits of both frame types in one design is challenging with established methods, with each architecture excelling in particular performance aspects whilst accepting compromises on others.

This is particularly important for road bikes that need to perform a variety of roles. Touring riding needs stability and predictability at normal speeds, especially when carrying luggage and a passenger. But circuit riding needs quick handling, precise steering feel, and maximum cornering grip. Most production bikes have fixed chassis settings that can't change between these different uses, being manufactured somewhere between stable and agile rather than allowing rider adjustment.

4.3 Current Adjustable Solutions

An adjustable system could solve this problem. In Gadola et al. (2019) paper, they built a prototype that provided independent adjustability of the steering angle, trail distance, and anti-dive setting without needing to take the bike apart in a workshop. Their system allowed the trail to be adjusted from 81mm up to 138mm, which would transform the bike from agile sports to a more stable touring setup. Instead of being a fixed compromise, it becomes something the rider can tune for different situations.

Palanivendhan et al. (2020) tested a hybrid chassis that combined features from both trellis and perimeter frames, trying to get stiffness values somewhere between the two. Their computer simulations suggested this might balance straight-line stability with cornering ability better than either frame type on its own. Even though this hybrid couldn't be adjusted by riders, it showed that the best performance might not be at either extreme.

A recent production motorcycle demonstrates adjustable chassis stiffness for road riders. Bimota's 2026 KB998 Rimini features what the company describes as "adjustable rigidity", as shown in Figure 1, based on their racing frame experience (Bimota), although the specific mechanism for this is not detailed in available literature. This means riders can actually tune the frame's stiffness and flex characteristics, not

just suspension or geometry settings. The frame combines chromoly tubes with CNC-machined aluminium plates, optimising the balance between flex and rigidity. In addition to a variable chassis flex system, Bimota includes pivot and eccentric adjusters for chassis geometry changes using basic tools. This shows that directional stiffness concepts from racing can now be offered as adjustable features for everyday riders to tune for different riding situations.




Figure 1 Shows 2026 Bimota KB998 Rimini frame. ("Bimota, 2025")

5 Conclusion

Putting together adjustable geometry and variable chassis stiffness seems like it could work well for bikes that need to do both road and circuit riding. But there's still a gap between what works on racetracks and what's practical for road bikes. Gadola et al. (2019) mentioned that there's a substantial difference between what you can measure with instruments and what riders actually experience through bike feel. Steering feedback and how the bike responds are most critical to riders, but these intangibles aren't thoroughly understood except by manufacturers' extensive testing.

All the authors agree that frame stiffness affects how motorcycles handle, and that varying types of stiffness have different effects. Cameron (2018), Kawata (2015), and Lake et al. (2012) all support the idea that lateral flexibility can be beneficial. However, there's some inconsistency around how much stiffness is actually needed and whether current designs are already optimal.

Kawata (2015) clearly explains why Suzuki needed to develop the low lateral stiffness frame for racing performance. Gadola et al. (2019) explicitly state that their work addresses the gap between what engineers can measure and what riders actually feel.

However, significant challenges remain before widespread adoption. Testing protocols linking chassis adjustments to rider feedback are needed, alongside safety validation across different settings and road conditions. Whether adjustable chassis systems become mainstream or remain specialist features will depend on better understanding how riders perceive and benefit from these adjustments in real-world use.

6 References

bimota [WWW Document], n.d. URL <https://www.bimota.com/it/en/> (accessed 11.8.25).

Cameron, K., 2018. Flexible Genius. *Cycle World* 24-26,28.

Gadola, M., Chindamo, D., Vitale, F., Bonera, E., 2019. The Design of A Motorcycle Featuring Fully Independent Adjustability for Front Suspension and Steering Geometry. *IOP Conf. Ser. Mater. Sci. Eng.* 538, 012064. <https://doi.org/10.1088/1757-899X/538/1/012064>

Kawata, K., 2015. Development of a Motorcycle Frame with Low Stiffness in the Side Direction for Racing. Presented at the JSAE/SAE 2015 Small Engine Technologies Conference & Exhibition, Osaka, Japan, pp. 2015-32-0839. <https://doi.org/10.4271/2015-32-0839>

KB998 Rimini [WWW Document], n.d. URL <https://www.bimota.com/it/en/kb998> (accessed 11.8.25).

Lake, K., Thomas, R., Williams, O., 2012. The influence of compliant chassis components on motorcycle dynamics: an historical overview and the potential future impact of carbon fibre. *Veh. Syst. Dyn.* 50, 1043-1052. <https://doi.org/10.1080/00423114.2011.647824>

Palanivendhan, M., Senthilkumar, S., Chandradass, J., Reddy, V., Raju, P., 2020. Design and development of hybrid chassis for two wheeler motorcycle. *IOP Conf. Ser. Mater. Sci. Eng.* 993, 012129. <https://doi.org/10.1088/1757-899X/993/1/012129>

Sakai, H., 2024. Revealing the Impact of Motorcycle Caster Angles on Weave and Wobble: A Comprehensive Analysis through Visualized Stability Testing. Presented at the WCX SAE World Congress Experience, Detroit, Michigan, United States, pp. 2024-01-2770. <https://doi.org/10.4271/2024-01-2770>

Sharp, R.S., 2001. Stability, Control and Steering Responses of Motorcycles. Veh. Syst. Dyn. 35, 291–318. <https://doi.org/10.1076/vesd.35.4.291.2042>