

Securing the Enterprise Network with Check Point Gaia R81.20

Portfolio Part 2 (80%) | Practical Demonstration
SMS Deployment | Firewall Policy | Threat Prevention | Verification

Smit Brijeshkumar Patel

Enrollment: 2506590 | Level 7 | MSc Cyber Security and Digital Forensics

University of Wales Trinity Saint David - London Campus

Presented: April 2026

What I'll Cover Today

Walking through the Part 2 build, end to end

01

The Scenario

Two-site enterprise network and what we were asked to secure.

02

SMS & SmartConsole

Installing A-SMS and A-GW on Gaia R81.20, establishing SIC trust, applying licences [1].

03

Firewall Policy

19 rules covering management, web, SSH, ICMP, FTP, DHCP, App Control and a final cleanup drop [2].

04

Advanced Features

Application Control, URL Filtering, IPS, Identity Awareness [3], [4].

05

Verification

DNS, DHCP, HTTPS, SSH and rule-blocking tests from real client machines.

06

Limitations & Wrap-up

Honest review of what worked, what didn't, and what I'd do differently.

A note on the lab. Everything you'll see today was built from scratch in VirtualBox - one Gaia SMS, one Gaia gateway, two Windows clients, a domain controller, and a SmartConsole admin workstation. A few things didn't go to plan; I'll be upfront about those at the end.

The Scenario

Two sites, one Check Point gateway, one job: lock it down

What We Started With

Two sites: SWANSEA.ACCA (HQ) and LONDON.SWANSEA.ACCA (branch). Connected over a simulated WAN through the Check Point gateway.

Core services running: Active Directory and DNS on S-DC, DHCP on the same box, IIS web server (HTTPS), and two domain-joined client workstations - one per site.

The job for Part 2: drop a Gaia SMS into this design, install a SmartConsole, get the gateway under management, write a sensible firewall policy, and turn on the protections that a real enterprise would actually use [1].

Key IP Addresses

A-SMS	10.1.1.101	Security Mgmt Server
A-GW	10.1.1.1	Gateway (mgmt int.)
A-GUI	10.1.1.201	SmartConsole admin
S-DC	192.168.1.1	DC / DNS / DHCP / IIS
ClientS1	192.168.1.10	Swansea client
L-CD	192.168.2.1	London branch device
ClientL1	192.168.2.10	London client

Note: S-DC handles DNS, DHCP, IIS and the domain controller role. That's a deliberate lab simplification - in a real deployment those would sit on separate hardened hosts [5].

Question 1 - Gaia Appliances and the SMS

Modifying the topology and bringing the management plane online (30%)

What I Built

A-SMS Check Point Gaia R81.20 Security Management Server. 10.1.1.101 [1].

A-GW Gaia R81.20 Security Gateway. eth0 = 10.1.1.1 (management), with three more interfaces wired for the WAN side.

A-GUI Windows 10 admin workstation at 10.1.1.201, running SmartConsole R81.20.

Pieces between them: SIC trust, certificate exchange, licences applied through SmartUpdate.

Why It Matters

Without a Security Management Server, every gateway has to be configured by hand and there's no central place to write or push policy. The SMS is what lets us treat the network as one system - one rulebase, one log stream, one set of objects shared across sites [1].

In other words, the SMS is the foundation everything else in this presentation sits on. If A-SMS doesn't trust A-GW, there is no policy to push.

1. Install & configure A-GW, A-SMS, A-GUI • 2. License the SMS • 3. Connect Swansea network to A-SMS

A-SMS - Gaia Portal Login

Security Management Server up and reachable on 10.1.1.101

What's on screen

Gaia web portal of A-SMS, accessed from the admin workstation at <https://10.1.1.101>.

Build: Check Point Security Management R81.20, kernel 3.10.0-1160.15.2cpx86_64, build 634, 64-bit, on Open Server [1].

Right pane shows the management blades available for activation - Firewall, IPSec VPN, IPS, Application Control, URL Filtering, Anti-Virus, Anti-Bot, Threat Emulation and Threat Extraction. We come back to several of these in Q3 [3].




Figure 1 - A-SMS Gaia portal showing R81.20 system info

A-GW - Network Interfaces

Gateway interfaces configured for management and WAN traffic

Interface plan

eth0	10.1.1.1 / 24	Management (same subnet as A-SMS)
eth1	192.168.1.254 / 24	Inside (Swansea LAN)
eth2	20.0.0.1 / 30	WAN to London (point-to-point)
eth3	10.0.5.15 / 24	VirtualBox NAT (internet access)
lo	127.0.0.1	Loopback

Why this wiring: eth0 shares a subnet with A-SMS so SIC negotiation works without routing tricks. eth1 is the Swansea LAN side — traffic from ClientS1 and S-DC exits here. eth2 is the /30 WAN link to L-CD in London. eth3 (10.0.5.15) is the VirtualBox NAT — this is why IPS signature updates failed; A-GW couldn't route back out through NAT to reach Check Point's update servers.




Figure 2 - A-GW Gaia portal: configured network interfaces

SmartConsole R81.20 - Connecting to A-SMS

From A-GUI to A-SMS as the 'Smitpatel' admin user

The connection in plain English

SmartConsole is the GUI we use to talk to the SMS. Without it, every change goes through Gaia CLI [1].

Login target: 10.1.1.101 (A-SMS).

User: Smitpatel - created during the SMS first-time wizard.

Build: R81.20.9700.633.

Once authenticated, SmartConsole pulls down the existing object database, policies and logs from A-SMS. Anything I change here gets staged as a 'session' and only goes live when I publish it - a useful safety net while learning.




Figure 3 - SmartConsole login dialog connecting to A-SMS at 10.1.1.101

Gateways & Servers - SIC Trust Established

Both A-GW and A-SMS visible, healthy, and managed

What this view confirms

● **A-GW** 10.1.1.1

Status OK, R81.20, CPU 12%

● **A-SMS** 10.1.1.101

Status OK, R81.20, CPU 17%

SIC trust (Secure Internal Communication) is the bit that took the longest. The gateway and the SMS exchange certificates over an activation key, and from that point every command between them is encrypted and authenticated [1].

If SIC is broken, the gateway shows up but you can't push policy. 'Trust established' on both is the green light to start writing rules.




Figure 4 - SmartConsole Gateways & Servers: A-GW and A-SMS healthy

Licensing the Management Server

Applied through SmartUpdate, status verified in SmartConsole

A-SMS

Lab evaluation licence applied via SmartUpdate. Tied to the SMS IP (10.1.1.101) and the host fingerprint - it won't work if either changes [1].

A-GW

Gateway licence attached after SIC was up. License Status surfaces in the gateway summary tab - useful at a glance during incidents.

Expiration

Expiry date checked in the licence properties pane. Documented in the report appendix so the next person picking this up isn't caught out.

Why I'm spending a slide on this

Licences are the silent failure point in Check Point deployments. A gateway can be up, SIC can be fine, the policy can be installed - and then traffic still doesn't flow correctly six weeks later because a blade licence quietly expired [1]. Documenting status and expiry up front is one of those small things that saves real grief later.

Question 2 - Writing the Firewall Policy

19 rules built around a default-deny posture (30%)

Default deny

If the policy doesn't explicitly allow it, the cleanup rule drops it. No 'Any-Any-Allow' anywhere [2].

Specific over generic

Where I could name a host, I named it. Allow_Admin_SSH targets the workstation, not 'any internal'.

Symmetric thinking

Every allow has a matching question: who initiates this, why, and what could it be misused for if the source is wrong?

Logging on by default

Drop rules log so I can see what's being attempted. Allow rules log so I can audit [6].

Real-world thinking

Treated as if this were a small enterprise where Swansea staff need to browse the web, hit the internal IIS server, and resolve internal DNS - while a separate admin needs SSH to the management plane. Telnet, FTP, ICMP from outside, and unsolicited inbound traffic are all dropped. SSH is allowed only from the admin workstation, not from a regular client - one of the more useful tests later [6].

Network Objects in SmartConsole

Defining who and where, before defining what they can do

Why objects come first

A rulebase that uses raw IP addresses ages badly. As soon as someone re-IPs a subnet, every rule that touched it has to be rewritten by hand. Defining named objects first means rules read in plain English and changing an IP is a one-place edit [2].

Networks

Swansea_LAN 192.168.1.0/24

London_LAN 192.168.2.0/24

Hosts: S-DC, ClientS1, ClientL1, L-CD, Admin_Workstation





Figure 5 - Network and Host objects in SmartConsole's object explorer

Firewall Rules 1-8 - Management and Web Traffic

First half of the policy: who reaches what, on which ports

What these rules say

- 1 Allow_Management_Access
Admin -> Any (any service)
- 2 Allow_GW_to_AD
A-GW -> S-DC
- 3 Allow_SMS_to_AD
A-SMS -> S-DC
- 4 Allow_Internal_DNS
LANs -> S-DC (DNS)
- 5 Allow_HTTPS_to_webServer
Any -> S-DC (HTTPS)
- 6 **Block_HTTP_to_webServer**
Any -> S-DC (HTTP) - DROP
- 7 Allow_Outbound_Web
LANs -> Any (HTTP/HTTPS)
- 8 Allow_Admin_SSH
Admin -> Any (SSH)



No.	Name	Source	Destination	Services & Applications	Action
1	Allow_Management_Access	Admin_Workstation	* Any	* Any	Accept
2	Allow_GW_to_AD	A-GW	S-DC	* Any	Accept
3	Allow_SMS_to_AD	A-SMS	S-DC	* Any	Accept
4	Allow_Internal_DNS	Swansea_LAN London_LAN	S-DC	dns	Accept
5	Allow_HTTPS_to_webServer	* Any	S-DC	https	Accept
6	Block_HTTP_to_webServer	* Any	S-DC	http	Drop
7	Allow_Outbound_Web	Swansea_LAN London_LAN	* Any	http https	Accept
8	Allow_Admin_SSH	Admin_Workstation	* Any	ssh	Accept
9	Block_SSH_Others	* Any	* Any	ssh	Drop
10	Block_Telnet	* Any	* Any	telnet	Drop
11	Block_FTP	* Any	* Any	ftp	Drop
12	Allow_Internal_ICMP	Swansea_LAN London_LAN	Swansea_LAN London_LAN	icmp-requests	Accept
13	Block_External_ICMP	* Any	* Any	icmp-requests	Drop
14	Allow_S2S_VPN	Swansea_LAN	London_LAN	* Any	Accept
15	Allow_DHCP	* Any	* Any	dhcp-request	Accept
16	Block_HighRisk_Apps	Swansea_LAN	* Any	P2P_File_Sharing_A...	Drop

Figure 6 - SmartConsole Security Policy: rules 1-16 (rules 1-8 highlighted)

Firewall Rules 9-15 - Service Lockdown and ICMP

Second half: explicit drops for the noisy stuff

Where the policy bites

- 9 **Block_SSH_Others**
Any -> Any (SSH) - DROP
- 10 **Block_Telnet**
Any -> Any (telnet) - DROP
- 11 **Block_FTP**
Any -> Any (FTP) - DROP
- 12 **Allow_Internal_ICMP**
LAN <-> LAN (icmp)
- 13 **Block_External_ICMP**
Any -> Any (icmp) - DROP
- 14 **Allow_S2S_VPN**
Swansea_LAN -> London_LAN
- 15 **Allow_DHCP**
Any -> Any (dhcp-request)




Figure 7 - SmartConsole Security Policy showing rules 9-15

Rules 16-19 - App Control, URL Filtering, Cleanup Drop

Layer 7 protections and the last line of the policy

What gets blocked here

16 Block_Highrisk_Apps

Swansea_LAN, London_LAN -> Any (P2P File Sharing, Anonymizer, Remote Admin) - DROP

17 Block_Dangerous_URL

Any -> Any (Phishing, Malware, Spyware, Gambling, Hacking) - DROP

18 Block_SocialMedia_Standard

Standard_Users_Role -> Any (Social Networking) - DROP

19 Cleanup_Drop_ALL

Any -> Any -> Any - DROP (catch-all)




Figure 8 - SmartConsole rules 16-19 with App Control and URL categories

Why These Rules, Specifically

Mapping each rule to a real business or security need

Management isolation

Admin SSH from one workstation only. Stops a compromised user box from pivoting to the SMS or gateway [6].

DNS lock-down

Clients only resolve through S-DC. Stops DNS exfiltration and matches AD's split-horizon DNS [5].

External ICMP dropped

Reduces network reconnaissance. Internal ICMP stays for admin troubleshooting.

No HTTP, only HTTPS

Internal IIS serves over HTTPS. Blocking port 80 to S-DC removes a downgrade target.

Telnet & FTP killed

Cleartext credentials in 2026 are inexcusable. SCP for any actual file transfer needs.

P2P & anonymisers

Both common malware C2 channels and a classic data-loss vector. Off by default is the right call [3].

Question 3 - Threat Prevention (IPS)

Custom IPS profile, signatures pulled, traffic inspected at L4-L7 (20%)

What's enabled

On A-GW > Threat Prevention tab:

- IPS blade with a Custom Threat Prevention profile (Optimised baseline) [3].
- SandBlast modules (Threat Emulation, Extraction, Zero Phishing) off in this lab.
- Anti-Bot and Anti-Virus visible but not activated for the demo.

What IPS does here: inspects traffic against Check Point's signature feed for known exploits and protocol abuse, and either logs or drops based on the profile [4].




Figure 9 - A-GW Threat Prevention: Custom profile with IPS enabled

Network Security Blades - The Full Set

Application Control, URL Filtering, Identity Awareness, Content Awareness

Blade-by-blade summary

- **Firewall** Stateful filter carrying the 19-rule policy [2].
- **Application Control** 8000+ apps recognised at L7. Powers the P2P / anonymiser drops [3].
- **URL Filtering** Category-based web filter feeding Block_Dangerous_URL.
- **Identity Awareness** AD-based source identity. Backs Standard_Users_Role rule [4].
- **Content Awareness** Data-type recognition for DLP-style controls. Visible, kept minimal here.
- **Monitoring** Performance and traffic visibility for the lab walkthrough.





Figure 10 - A-GW Network Security blade set in General Properties

Verification - DNS Resolution and Connectivity

Allow-rules doing their job from the client side



```
Administrator: Command Prompt
Microsoft Windows [Version 10.0.19045.2000]
(c) Microsoft Corporation. All rights reserved.

C:\Users\Administrator>nslookup swansea.acca 192.168.1.1
Server: 5-DC.swansea.acca
Address: 192.168.1.1


Name: swansea.acca
Addresses: 192.168.1.1
          192.168.1.5
          20.0.0.1

C:\Users\Administrator>
```

nslookup swansea.acca

DNS resolves through 5-DC at 192.168.1.1. Returns the expected internal records (192.168.1.1, 192.168.1.5, 20.0.0.1). Rule 4 (Allow_Internal_DNS) confirmed [6].

Figure 11 - nslookup against internal DNS



```
Administrator: Command Prompt
Rec DHCP Server . . . . . : 192.168.1.2
DHCPv6 IAID . . . . . : 302514215
DHCPv6 Client GUID. . . . . : 00-01-00-01-31-67-3B-41-08-00-27-43-A9-39
DNS Servers . . . . . : 192.168.1.1
NetBIOS over Tcpip. . . . . : Enabled

C:\Users\Administrator>ping 192.168.1.1

Pinging 192.168.1.1 with 32 bytes of data:
Reply from 192.168.1.1: bytes=32 time=1ms TTL=128
Reply from 192.168.1.1: bytes=32 time=1ms TTL=128
Reply from 192.168.1.1: bytes=32 time=1ms TTL=128
Reply from 192.168.1.1: bytes=32 time=1ms TTL=128

Ping statistics for 192.168.1.1:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 1ms, Average = 0ms

C:\Users\Administrator>nslookup swansea.acca 192.168.1.1
Server: 5-DC.swansea.acca
Address: 192.168.1.1

Name: swansea.acca
Addresses: 192.168.1.1
          192.168.1.5
          20.0.0.1

C:\Users\Administrator>
```


ping 192.168.1.1

4/4 replies, sub-1ms RTT, 0% packet loss. Rule 12 (Allow_Internal_ICMP) holds. The DHCP info above the ping shows the client also picked up its lease cleanly.

Figure 12 - ping showing intra-LAN ICMP allowed

Verification - DHCP /release and /renew

Rule 15 (Allow_DHCP) traced end-to-end on ClientS1



```
Administrator: Command Prompt
Microsoft Windows [Version 10.0.19045.2006]
(c) Microsoft Corporation. All rights reserved.

C:\Users\Administrator>ipconfig /release

Windows IP Configuration

Ethernet adapter IntSwa:

    Connection-specific DNS Suffix  . : 
    Link-local IPv6 Address . . . . . : fe80::b01e:60bd:e343:2019%4
    IPv4 Address. . . . . : 192.168.1.10
    Subnet Mask . . . . . : 255.255.255.0
    Default Gateway . . . . . : 192.168.1.1

Ethernet adapter Ethernet:

    Connection-specific DNS Suffix  . : 
    Link-local IPv6 Address . . . . . : fe80::88ac:9377:bde8:c3c9%13
    Default Gateway . . . . . : 

C:\Users\Administrator>ipconfig /renew

Windows IP Configuration


Ethernet adapter IntSwa:

    Connection-specific DNS Suffix  . :
```

Step 1 - ipconfig /release

Client gives up its current lease on the IntSwa adapter (was 192.168.1.10, mask 255.255.255.0, gateway 192.168.1.1). Interface drops back to a link-local IPv6 address only - the release went through.

Figure 13 - ipconfig /release on ClientS1



```
Administrator: Command Prompt

C:\Users\Administrator>ipconfig /renew

Windows IP Configuration

Ethernet adapter IntSwa:

    Connection-specific DNS Suffix  . : 
    Link-local IPv6 Address . . . . . : fe80::b01e:60bd:e343:2019%4
    IPv4 Address. . . . . : 192.168.1.10
    Subnet Mask . . . . . : 255.255.255.0
    Default Gateway . . . . . : 192.168.1.1

Ethernet adapter Ethernet:

    Connection-specific DNS Suffix  . : communityfibre.co.uk
    Link-local IPv6 Address . . . . . : fe80::88ac:9377:bde8:c3c9%13
    IPv4 Address. . . . . : 192.168.1.6
    Subnet Mask . . . . . : 255.255.255.0
    Default Gateway . . . . . : 192.168.1.1

C:\Users\Administrator>
```


Step 2 - ipconfig /renew

Client broadcasts DHCPDISCOVER, S-DC's DHCP service answers, and the same 192.168.1.10 address is leased back. Rule 15 (Allow_DHCP, dhcp-request service) lets the broadcast/unicast exchange traverse the gateway [6].

Figure 14 - ipconfig /renew restores the lease


Verification - HTTPS Allowed, HTTP Blocked

Rule 5 and Rule 6 - same target, different protocol, different outcomes



IIS welcome page renders. Rule 5 (Allow_HTTPS_to_webServer) lets the TLS handshake reach S-DC on port 443. DNS, gateway routing and the IIS binding all work.

Figure 15 - HTTPS to S-DC permitted by Rule 5




ERR_CONNECTION_REFUSED. Rule 6 (Block_HTTP_to_webServer) drops the SYN before it gets to port 80 - browser never sees a server response [6].

Figure 16 - HTTP to S-DC dropped by Rule 6

Verification - SSH and FTP


Same protocol, different sources, different outcomes



SSH from Admin (A-GUI)

ALLOWED


Login successful. Rule 8 (Allow_Admin_SSH) lets the admin workstation through to A-SMS on port 22.



SSH from ClientS1

REFUSED

'Connection refused' on port 22. Rule 9 (Block_SSH_Others) drops everything that isn't the admin workstation [6].



FTP from ClientS1

REFUSED

'ftp: connect : Connection refused' on port 21. Rule 11 (Block_FTP) drops the connection - no cleartext file transfer leaving the LAN.

Figure 17 - SSH from admin: allowed

Figure 18 - SSH from client: refused

Figure 19 - FTP from client: refused

What Didn't Go to Plan

Honest review of the rough edges and what I'd do differently

IPS signature update failed

A-GW runs behind a VirtualBox NAT (10.0.5.x) and couldn't reach its upstream gateway on the host network. The cpview update job timed out. Workaround: 'ignore errors and continue'. Real fix: bridged adapter or a host-only network with proper routing [3].

Identity Awareness LDAP didn't bind

AD LDAP connection failed for the same lab routing reason - A-GW couldn't reach S-DC on 389/636 reliably. Standard_Users_Role still works because identity is sourced via Identity Collector for the demo, but I'd want a clean LDAP bind in production [4].

Same-subnet traffic doesn't traverse A-GW

ClientS1 to S-DC is intra-subnet, so the firewall doesn't see it. The rules that show up in logs are the ones crossing zones (LAN to gateway, LAN out to WAN). Tested cross-subnet behaviour to compensate.

Self-signed certificate noise

Browser warnings on Gaia portal and IIS are expected - documented but not replaced. In a real environment a small internal CA solves it cleanly [5].

Conclusion and Recommendations

Key Findings

Working Gaia R81.20 management plane built on the Part 1 topology - SMS, gateway, SmartConsole, SIC trust, licensing.

19-rule firewall policy with default-deny posture, identity-aware blocking, Layer 7 controls via App Control and URL Filtering.

Verified end-to-end from real client machines: DNS, DHCP, HTTPS allow / HTTP block, SSH source-based decision, FTP block.

IPS and Identity Awareness configured but constrained by lab routing - both work in principle and would be straightforward to fix on a real network.

Recommendations

Replace VirtualBox NAT with bridged or host-only routing so IPS signature feeds and AD LDAP bind work cleanly [3], [4].

Replace self-signed certs with an internal CA on Gaia portal and IIS - removes browser warnings and prevents a real downgrade vector [5].

Enable Anti-Bot, Anti-Virus and Threat Emulation once licences allow - the policy framework is already in place.

Schedule monthly licence and signature health checks; document expiry dates in the operations runbook [1].

Thank You | Q & A

References

- [1] Check Point Software Technologies, R81.20 Security Management Administration Guide. Tel Aviv, Israel: Check Point Software Technologies Ltd., 2023.
- [2] Check Point Software Technologies, "Quantum Security Gateway Best Practices for Access Control Policy," sk108600, 2024. [Online]. Available: <https://support.checkpoint.com>
- [3] Check Point Software Technologies, R81.20 Threat Prevention Administration Guide. Tel Aviv, Israel: Check Point Software Technologies Ltd., 2023.
- [4] Check Point Software Technologies, R81.20 Identity Awareness Administration Guide. Tel Aviv, Israel: Check Point Software Technologies Ltd., 2023.
- [5] K. Scarfone and P. Hoffman, "Guidelines on Firewalls and Firewall Policy," NIST Special Publication 800-41 Rev. 1, National Institute of Standards and Technology, Gaithersburg, MD, 2009.
- [6] W. Stallings, Network Security Essentials: Applications and Standards, 6th ed. London, U.K.: Pearson, 2017.
- [7] R. Bejtlich, The Practice of Network Security Monitoring: Understanding Incident Detection and Response. San Francisco, CA: No Starch Press, 2013.
- [8] M. Lucas, Networking for System Administrators. Detroit, MI: Tilted Windmill Press, 2015.