

Web Services x OOP

by Jeffery Aideyan-Ohonba

Submission date: 01-May-2025 04:06PM (UTC+0100)

Submission ID: 257474303

File name: 58851_Jeffery_Aideyan-Ohonba_Web_Services_x_OOP_664183_403321302.pdf (295.53K)

Word count: 4918

Character count: 31124



WEB SERVICES X OBJECT ORIENTED PROGRAMMING



Jeffery Aideyan-Ohonba - 2420646

Table of Contents

Introduction.....	2
Conceptual foundations.....	2
Encapsulation	2
Inheritance.....	3
Polymorphism	3
Abstraction	4
Overview of Web Services	4
RESTful Architectures	5
Object-relational mapping (ORM) in Web Services	6
Advantages and Limitations of ORM in large-Scale Web Applications.....	7
Spring Boot and OOP	7
How Spring Boot integrates with OOP concepts to enhance maintainability, modularity, and reusability.....	7
Design patterns used in Spring Boot	8
Dependency Injection	8
Best practices in designing a scalable and efficient web service using Spring Boot and ORM.....	9
Challenges and Future Perspectives	10
Common Challenges faced when implementing OOP-based web services with ORM...	10
Emerging Trends in Web Service Architectures and their implications on OOP and ORM	11
Microservices & Cloud-native Development	11
GraphQL APIs	12
Recommendations for Improving ORM strategies in Large-Scale Enterprise Applications	13
Conclusion	15
References	15

Introduction

In modern software development, Object-Oriented Programming (OOP) and Web Services play pivotal roles in designing efficient, scalable systems. OOP principles such as encapsulation, inheritance, polymorphism, and abstraction have long been foundational in creating maintainable and modular software. Meanwhile, the increasing need for distributed systems, especially in the era of microservices and cloud-native architectures, has brought forward the essential role of web services in ensuring seamless communication between components. In particular, technologies like Spring Boot and Object-Relational Mapping (ORM) frameworks, such as Hibernate, provide developers with powerful tools to simplify database interactions and build responsive, scalable web services. This paper explores the intersection of OOP and web services, examining best practices, challenges, and emerging trends in the development of modern, high-performance systems. It also delves into the critical role that ORM plays in managing data in large-scale enterprise applications, offering recommendations for optimising its use in real-world scenarios.

Conceptual foundations

This section will analyse the core principles of Object Oriented Programming: encapsulation, inheritance, polymorphism, and abstraction, highlighting their role in software design and development.

Encapsulation

Encapsulation in OOP is all about keeping certain parts of a class like its internal data and member functions out of reach from the outside world. It's essentially a way of protecting the internal state of an object by exposing only what's necessary through a controlled interface. As described in [1], encapsulation doesn't just mean hiding variables or making everything private for the sake of it. The bigger picture is about reducing unnecessary mental effort during design. When we don't have to constantly think about every inner working of a class, we can focus on the broader structure and

higher-level abstractions of the system. This is especially powerful in large-scale applications, where well-encapsulated components can be built, understood, and debugged independently. A good rule of thumb, as suggested in the source, is to keep all class data private unless there's a solid reason not to [1].

Inheritance

Inheritance is a core part of object-oriented programming (OOP), letting one class reuse code from another in an easy and natural way. The concept defines an “is-a” hierarchy, meaning that a subclass inherits from a superclass and can either extend or modify its behaviour. For example, a car *is a* vehicle. This mirrors how we often introduce new concepts in real life - by comparing them to something familiar [2].

There are generally two types of inheritance: single and multiple. Single inheritance allows a class to inherit from just one super class, even across multiple levels of the hierarchy. Multiple inheritance, on the other hand, means a class can inherit from more than one class at the same time, like a graphical image inheriting properties from both a geometrical shape and a picture [3].

In Java, inheritance is limited to the single type. This avoids issues like the “diamond problem”, where a subclass could inherit conflicting methods or attributes from multiple super classes that share a common ancestor. When that happens, the subclass may struggle to resolve which version of a method to use. To support shared behaviour across different class types without running into these problems, Java uses interface instead [3].

Polymorphism

Polymorphism is one of the most powerful OOP concepts that makes designing and extending code a whole lot easier. It basically lets you write one method that works in different ways depending on what object it's working with. This keeps your code clean, avoids repetition, and makes it easier to update things later on without breaking everything.

There are two common ways of applying polymorphism: overloading and overriding. Overloading is when you've got methods with the same name but different parameters. This is good for keeping things simple when you're doing similar tasks that just need slightly different inputs. But if you overdo it, it can get confusing, especially when it's not clear which version is actually being used.

Overriding is when a subclass takes a method from its parent class and provides its own version. This is the key part of polymorphism that lets objects behave differently even when they're being called through the same method name [4].

Abstraction

Abstraction is all about focusing on what a class or piece of code *does*, without getting caught up in the details of *how* it does it. It's a way of modelling software by showing the necessary parts and hiding everything else that's not immediately important. This makes it easier to design and reason about systems, because you're not constantly focused on implementation details [1].

This idea extends beyond just classes and methods. In the OOP world, as stated in [1], abstraction also helped drive developments like template functions and classes, which formed the basis for tools like the Standard Template Library (STL). These tools laid the groundwork for generic programming and metaprogramming, which allow developers to write generalised code that can adapt to specific types later during compilation. In many cases, compilers are now doing more of the heavy lifting, generating and executing code behind the scenes, with only the final results being used in the program.

As OOP became more widely adopted, developers started recognising common structures and relationships between classes that kept repeating across different projects. This is where design patterns came in as abstract solutions to recurring design problems that improve code readability, maintainability, and reusability [1].

Overview of Web Services

As enterprises started dealing with more distributed systems and data, integrating everything across different platforms became a major challenge. Service-Oriented

Architecture (SOA) was introduced to solve issues of tight coupling, and web services became the main way to implement it [5].

Traditional web services, defined by W3C, are software systems that enable machine-to-machine communication over a network [6]. They rely on SOAP for messaging, WSDL for describing services, and UDDI for publishing and discovering them. This setup enables interoperability and decouples systems across different platforms and languages [5].

Still, they come with limitations, useful information is often hidden behind a single POST endpoint, the SOAP messaging process is complex and slow, and clients are tightly bound to WSDLs. The overhead from SOAP and WSDL also hurts performance and makes caching difficult [5].

These drawbacks opened the door for REST to gain traction, something we'll explore next.

RESTful Architectures

REST, which stands for Representational State Transfer, is an architectural style that offers a simpler alternative to traditional Web Services. It was originally introduced as a way to improve how distributed hypermedia systems are designed, and later became a guideline for shaping modern Web architecture [5]. What makes REST stand out is how it builds on existing, widely-used Web standards like HTTP, URIs, and MIME types, which makes it simple and easy to adopt in real-world systems.

At the heart of RESTful Web Services is the idea of resource, which refers to any identifiable entity on the Web. These resources are accessed using standard HTTP methods (like GET, POST, PUT, and DELETE), and they're represented in formats such as XML or JSON, which include both the actual data and metadata about it. The interaction is built around the idea of content negotiation, where clients and servers agree on the most suitable format for exchanging information. As described in [5], working with a RESTful Web Service is very similar to navigating a dynamic website.

RESTful Web Services come with several strengths. They are addressable, meaning every resource has a unique URL, making it directly accessible without needing a

central registry like UDDI. They are also stateless, meaning each request stands on its own, carrying all the necessary info needed to process it without relying on previous interactions. REST uses a uniform interface, simplifying how services are consumed since the same HTTP methods apply across the board. Plus resources are linked together using hyperlinks, enabling state transitions through the web itself.

Relevance to modern software engineering

These qualities make RESTful Web Services lightweight, easy to use, and highly scalable. These are qualities that are especially valuable in modern software engineering. As [5] notes, their simplicity and flexibility have made them a go-to choice for companies like Google, Amazon, and eBay. REST now powers around 66% of all public APIs listed on “ProgrammableWeb” [5].

Object-relational mapping (ORM) in Web Services

Object-Relational Mapping (ORM) is a technique that allows object-oriented applications to interact with relational databases without requiring direct SQL manipulation. Instead of writing low-level code for every query, developers work with program objects, while the ORM framework maps these objects to relational tables behind the scenes [7]. This is particularly valuable in web applications, where multithreading and concurrent access can introduce complexity.

Hibernate, one of the earliest and most influential ORM frameworks, was designed to simplify the persistence layer in Java applications. According to [7], Hibernate handles everything from object-to-table mapping to managing relationships and executing queries, allowing developers to work entirely in the object-oriented paradigm. Updates to objects are tracked automatically, and the necessary database operations are performed at commit time.

A key strength of tools like Hibernate is the use of the Entity Model, which acts as a bridge between application logic and database structure. This model aims to abstract away complex table relationships and enables developers to design around objects and their association, including advanced features like inheritance hierarchies without worrying about how they'll be implemented in SQL [7].

By automating tedious persistence logic and making database access feel native to the language, ORM tools significantly improve development speed, code maintainability, and scalability in modern service-based applications.

Advantages and Limitations of ORM in large-Scale Web Applications

While not strictly required for database interaction, ORM tools save developers a lot of time and effort. Without them, managing persistence means writing low-level SQL queries manually, then converting the results back into usable objects. This not only slows down development, but also makes the code harder to read and maintain, especially as the application grows and evolves. ORM engines handle all of that automatically and often validate the generated SQL at startup, which helps catch issues early. As noted in [8], this built-in validation can be a good way to ensure the data model and the object stay in sync.

That said, ORMs aren't perfect. According to [8], some well-known developers have pointed out that ORM tools often fall short when it comes to fully bridging the gap between object-oriented programming and relational databases. Joel Spolsky famously called ORMs "leaky abstractions" because they tend to expose the complexity they're meant to hide. Ted Neward went even further, comparing ORM to the "Vietnam War", suggesting it only gets messier as you try to support more advanced features. Martin Fowler also called ORM a "hard problem", arguing that in many cases, these tools simply can't meet all the demands of relational persistence. All of these issues trace back to the core problem: object-oriented and relational database systems don't line up neatly, a disconnect often referred to as impedance mismatch [8].

Spring Boot and OOP

How Spring Boot integrates with OOP concepts to enhance maintainability, modularity, and reusability

Spring Boot's integration with core object-oriented principles plays a major role in making code more maintainable, modular, and reusable. One of the standout features is its use of dependency injection, which helps keep classes loosely coupled and easy to test. Instead of relying on static code (which is notoriously hard to work with), Spring

encourages injecting dependencies through constructors. This not only turns classes into simple POJOs that can be tested independently, but also helps prevent common pitfalls like null pointer exceptions when new dependencies are introduced [9].

Another key principle in play is the Law of Demeter, also known as the “principle of least knowledge.” This rule promotes encapsulation by encouraging objects to only interact with their immediate “friends” rather than reaching deep into other objects’ internals. Following this pattern helps avoid tangled code and makes components easier to modify or reuse without breaking other parts of the system [9]. By leaning into these OOP practices, Spring Boot sets developers up for building applications that are cleaner, more testable, and easier to evolve over time.

Design patterns used in Spring Boot

Dependency Injection

Spring Boot’s use of the Dependency Injection (DI) design pattern is deeply tied to object-oriented principles like abstraction and encapsulation, which in turn promotes qualities like modularity and reusability. Through its IoC container, Spring manages the full lifecycle of application components known as beans, from creation to destruction, removing the need for tightly coupled code. Developers can inject dependencies using annotations like `@Autowired`, allowing classes to declare what they need without worrying about how to construct it. This makes the codebase more maintainable and easier to test. DI also encourages interface-driven design, where implementations can be swapped behind shared interfaces. For example, [10] describes how both `CarService` and `TruckService` implement the `VehicleService` interface, allowing Spring to inject the appropriate class depending on the configuration. When multiple implementations exist, Spring provides tools like `@Qualifier` or explicit naming to resolve ambiguity. Whether wired through constructors or setters, this approach makes the system more modular, while keeping each class focused on a single responsibility, which are all key traits of well-structured OOP [10].

Best practices in designing a scalable and efficient web service using Spring Boot and ORM.

Designing scalable and efficient web services with Spring Boot and ORM technologies like Hibernate relies on several proven best practices. According to [11], these practices are key to maintaining performance while handling growing workloads.

Scaling strategies are an important consideration when designing scalable web services, and a key best practice is to choose the most suitable approach based on the application's architecture and expected workload. As highlighted in [11], horizontal scaling, where more machines are added to distribute traffic is ideal for cloud-native and high traffic applications, while vertical scaling, which strengthens a single machine's resources, is suited for simpler or budget-limited projects.

Another essential practice is implementing appropriate database division techniques. As stated in [11], database sharding, which splits a database into independent shards, is crucial for handling very large datasets and improving write-heavy performance, especially in globally distributed systems. Partitioning, which breaks large tables into smaller parts, is similarly important for optimising queries and managing large volumes of data efficiently.

Efficient connection management is another recommended best practice. Using connection pooling libraries such as HikariCP, reduces connection overhead, improves concurrent request handling, and avoids blocking issues. Load balancing also matters, by spreading database queries across multiple servers, it helps keep systems responsive and avoids overloading any one server.

Read-write separation is also emphasised as a best practice for scalability. According to [11], setting up a master-slave database architecture ensures that read queries are offloaded to replicas, while write operations are directed to the master, helping balance workloads. Eventual consistency mechanisms are used in distributed systems to maintain synchronisation without introducing significant performance penalties.

Finally, tuning Hibernate's settings can give extra performance benefits. As recommended in [11], enabling connection pooling, using second-level caching,

processing database updates in batches, and setting smart fetch sizes all help lower response times and improve how the service scales.

By applying these best practices thoughtfully, developers can build Spring Boot and ORM web services that stay fast, reliable, and ready to handle real-world growth.

Challenges and Future Perspectives

Common Challenges faced when implementing OOP-based web services with ORM

Implementing OOP-based web services using ORM frameworks like Hibernate brings significant benefits in abstraction and developer productivity, but also introduces several recurring challenges. These often emerge from how ORM tools hide the details of database management behind object-based APIs. As discussed in [12], this abstraction prevents compilers from optimising database interactions. It also limits the developer's visibility into how data flows through the application. As a result, developers may unknowingly introduce performance issues as their applications scale.

One common issue is related to lazy and eager loading. As shown in [13], if relationships between entities are configured with eager loading, it can cause the application to load large amounts of unnecessary data even if only a small part is needed. This excessive data retrieval increases memory use and slows down response times, particularly when scaling up the number of records. For example, in a simple application managing companies and departments, fetching associated department records eagerly, even when they weren't needed, significantly impacted performance. After switching to lazy loading, the response time improved by 71%, demonstrating how important it is to configure loading strategies appropriately.

A closely related challenge is the one-by-one processing anti-pattern, where the ORM generates separate queries for each individual record in a loop, commonly leading to what's known as the N+1 problem. Instead of retrieving related data in bulk, the application ends up issuing a separate query for every related item, severely impacting performance. [13] shows that batching techniques (such as setting a batch size) can

help mitigate this issue by grouping data fetches, though solutions often depend on the specific application context.

While ORM tools raise the level of abstraction and speed up development, their design trade-offs often become limiting in big-data scenarios [12], especially when the system grows past hundreds of thousands of records. Developers frequently find themselves having to hand-tune ORM configurations or add caching manually, reintroducing complexity that ORM was meant to avoid in the first place.

Together, these performance pitfalls – eager loading, one-by-one processing, and the broader limitations of ORM abstraction, are key challenges when building scalable and efficient OOP-based web services. Understanding and addressing them early in the design process is crucial for delivering systems that remain performant as data and usage grow.

Emerging Trends in Web Service Architectures and their implications on OOP and ORM

Microservices & Cloud-native Development

With the rise of cloud-native applications, the way we build and deploy web services has changed dramatically. One of the biggest shifts has been the move from traditional monolithic systems to microservices architecture. Instead of building one large, tightly connected application, microservices break things down into smaller, independent services that each focus on a specific task. This makes it easier to scale parts of the system, release updates more frequently, and keep services running even if one component fails [14].

Cloud platforms are a perfect match for microservices. They give teams the flexibility to spin up or scale down resources as needed, which helps keep performance up and cost down. But while this model has many advantages, it also brings new challenges, especially around managing complexity, data consistency issues, and security concerns [14].

So where does OOP fit into all this? Interestingly, these new trends don't make OOP less relevant, in fact, they highlight its strengths. As noted in [15], OOP principles like

encapsulation, abstraction, and polymorphism are still incredibly useful in managing the complexity that comes with having so many separate services. By using these principles, developers can write services that are more modular and easier to maintain.

However, these trends also reshape how OOP is applied. Instead of designing large object hierarchies in a single codebase, developers now need to think about how individual services (each built using OOP concepts) communicate and evolve separately. Inheritance and shared logic need to be handled more carefully, especially when services are spread across different teams or even different languages [15]. The result is a shift in focus, from reusing code within a single application to building reusable, self-contained services that work well together.

Ultimately, microservices and cloud-native development push OOP in a new direction. They don't replace it, they reshape it. Developers still rely on core OOP ideas, but use them differently, placing more emphasis on isolation, interface design, and flexibility across boundaries. As systems become more distributed and complex, understanding how to apply OOP effectively in this new context becomes even more important [15].

GraphQL APIs

GraphQL, introduced by Facebook in 2015, offers a schema-driven approach to APIs that lets clients request exactly the data they need. As explained in [16], this helps avoid both over-fetching and under-fetching, making GraphQL especially useful when dealing with complex data structures or varied client requirements.

Rather than exposing multiple endpoints like REST, GraphQL uses a single endpoint to handle all operations: queries, mutations, and subscriptions, based on strongly typed schema. This schema-first design improves maintainability by serving as both a source of truth and live documentation.

Each GraphQL operation is backed by a resolver, a function that fetches or modifies the relevant data. These resolvers often reuse existing service logic. While [16] acknowledges that defining these components adds some overhead, it also enables code reuse and greater flexibility.

GraphQL is particularly well-suited for API gateway roles or aggregation layers in microservices systems, thanks to its ability to combine data from different services into a single schema. It is less common for direct services-to-service communication, where REST remains a simpler fit.

Schema evolution is another area where GraphQL offers benefits. New fields can be added without breaking existing clients, and deprecated fields can be removed over time. This minimises the need for versioning, a common issue in REST APIs. Tools like GraphQL playground also support debugging and exploration, streamlining development workflows.

While [16] does not explicitly focus on OOP or ORM, its discussion of schema-resolver architecture has practical implications for both. Since resolvers typically interact with existing service logic, which is often written in an object-oriented style, this encourages code reuse and separation of concerns. At the same time, developers may need to manage how schema types map onto ORM models, which can introduce some complexity and overhead, especially in larger systems.

In summary, GraphQL is a strong option for client-facing APIs that require flexibility and evolve frequently, while noting that simpler internal APIs may not benefit enough to justify the extra complexity.

Recommendations for Improving ORM strategies in Large-Scale Enterprise Applications

Optimising ORM strategies is essential for improving the efficiency and scalability of database interactions in large-scale enterprise applications. As highlighted in [17], ORM frameworks like Hibernate provide significant abstraction over direct database interactions, but they require careful tuning to ensure optimal performance. Several key strategies can be employed to address common challenges and enhance overall application efficiency.

1. Lazy vs. Eager Loading

A critical aspect of ORM performance is choosing between lazy and eager loading. Lazy loading fetches related entities only when they are explicitly required, thus minimising unnecessary database queries. In contrast, eager loading retrieves all related data in a single query, which can reduce the number of database calls but may increase memory usage. As noted in [17], configuring the loading strategy correctly, such as using `@OneToMany(fetch = FetchType.LAZY)` in Hibernate, is essential for balancing performance and resource usage. Developers should carefully consider the specific data access patterns of their applications to select the appropriate strategy.

2. Query Optimisation

Efficient query generation and execution are vital for reducing database load. The use of indexes, optimised SQL queries, and JOIN operations plays a key role in speeding up data retrieval. In particular, Hibernate Query Language (HQL) can be used to write more efficient queries that take advantage of ORM's abstraction while minimising database overhead. According to [17], applying query optimisation techniques not only enhances performance but also ensures that database interactions remain manageable as the application grows in complexity.

3. Batch Processing

In high-volume applications, reducing the number of queries sent to the database is a crucial performance improvement strategy. Batch processing allows multiple inserts or updates to be handled in a single operation, significantly decreasing the number of database round-trips. As demonstrated in [17], Hibernate's `hibernate.jdbc.batch_size` property can be used to enable batch processing, helping reduce the overhead associated with multiple individual queries. By leveraging batch processing, developers can greatly improve the efficiency of bulk data operations, which is especially important in large-scale enterprise systems.

Conclusion

Optimising ORM frameworks in large-scale enterprise applications involves a combination of careful tuning and best practices. The strategies of lazy versus eager loading, query optimisation, and batch processing are critical for reducing database

interaction time, improving application scalability, and ensuring better overall performance. By applying these strategies thoughtfully, organisations can enhance their ORM frameworks to meet the demands of complex, high-volume enterprise applications.

Conclusion

In conclusion, the integration of OOP principles with modern web service architectures, particularly through tools like Spring Boot and ORM technologies, has revolutionised the way we build scalable and maintainable systems. While the adoption of microservices and cloud-native applications presents new challenges, the core principles of OOP remain invaluable in managing complexity, ensuring modularity, and fostering reusability across distributed services. However, as we've seen, using ORM frameworks like Hibernate requires careful consideration, particularly when it comes to issues such as lazy and eager loading, query optimisation, and batch processing. By applying best practices and optimising ORM strategies, developers can overcome common performance pitfalls and create systems that remain efficient even as data and usage grow. As emerging trends like GraphQL APIs continue to reshape the landscape, the flexibility and power of OOP, coupled with smart ORM strategies, will remain key to building the next generation of high-performance software systems.

References

- [1] B. Cyganek, "Delving into Object-Oriented Programming," in *Introduction to Programming with C++ for Engineers*, United Kingdom: John Wiley & Sons, Incorporated, 2021, pp. 227–348. doi: 10.1002/9781119431152.ch4.
- [2] G. B. Singh, "Single versus multiple inheritance in object oriented programming," *OOPS messenger*, vol. 6, no. 1, pp. 30–39, 1995, doi: 10.1145/209866.209871.
- [3] F. Albalooshi and A. Mahmood, "A Comparative Study on the Effect of Multiple Inheritance Mechanism in Java, C++, and Python on Complexity and Reusability of Code," *International journal of advanced computer science & applications*, vol. 8, no. 6, 2017, doi: 10.14569/IJACSA.2017.080614.

- [4] H. Ali, M. Hamza, M. Y. Rashid, and T. A. Ahmed, "Exploring Polymorphism: Flexibility and Code Reusability in Object-Oriented Programming," *Passer Journal of Basic and Applied Sciences*, vol. 6, Special Issue, pp. 502-512, 2024, doi: 10.24271/psr.2024.189667.
- [5] J. Meng, S. Mei, and Z. Yan, "RESTful Web Services: A Solution for Distributed Data Integration," *2009 International Conference on Computational Intelligence and Software Engineering*, Wuhan, China, 2009, pp. 1-4. doi: 10.1109/CISE.2009.5365234
- [6] Xuan Shi, "Sharing Service Semantics using SOAP-Based and REST Web Services", *IT PRO.*, vol. 8, no. 2, pp. 18-24, March/Apri1 2006.
- [7] E. J. O'Neil, "Object/relational mapping 2008: hibernate and the entity data model (edm)," in *Proceedings of the 2008 ACM SIGMOD international conference on Management of data*, New York, NY, USA: ACM, 2008, pp. 1351-1356. doi: 10.1145/1376616.1376773.
- [8] G. Vial, "Lessons in Persisting Object Data Using Object-Relational Mapping," in *IEEE Software*, vol. 36, no. 6, pp. 43-52, Nov.-Dec. 2019, doi: 10.1109/MS.2018.227105428.
- [9] Muldoon, C., Görgü, L., O'Sullivan, J.J., Meijer, W.G. and O'Hare, G.M., 2021. Engineering testable and maintainable software with Spring Boot and React. *IEEE TRANSACTIONS ON SOFTWARE ENGINEERING*, p.1.
- [10] M. Bojkić, Đ. Pržulj, M. Stefanović, and S. Ristić, "Usage of Dependency Injection within Different Frameworks," in *Proceedings of the 19th International Symposium INFOTEH-JAHORINA*, Jahorina, Bosnia and Herzegovina, Mar. 2020, pp. 1-6.
- [11] B. Tanneru, "Designing Scalable Systems Using Spring Data and Hibernate ORM," *International Journal of Leading Research Publication (IJLRP)*, vol. 4, no. 9, pp. 1-5, Sept. 2023. [Online]. Available: <https://www.ijlrp.com/papers/2023/9/1273.pdf>
- [12] C. Yan, Z. Chu, A. Cheung, and S. Lu, "Database-Backed Web Applications in the Wild: How Well Do They Work?," *arXiv preprint arXiv:1607.02561*, 2016. [Online]. Available: <https://arxiv.org/abs/1607.02561>

[13] T. Chen, W. Shang, Z. M. Jiang, A. E. Hassan, M. Nasser, and P. Flora, "Detecting performance anti-patterns for applications developed using object-relational mapping," in *Proceedings of the 36th International Conference on Software Engineering (ICSE)*, Hyderabad, India, May 2014, pp. 1001–1012.

[14] P. R. R. Thumati, S. Eeti, M. Garg, N. Jindal, and P. K. Jain, "Microservices Architecture in Cloud-Based Applications: Assessing the Benefits and Challenges of Microservices Architecture for Cloud-Native Applications," *TIJER - International Research Journal*, vol. 11, no. 2, pp. 1–10, Feb. 2024. [Online]. Available: <https://tijer.org/tijer/papers/TIJER2402102.pdf>

[15] S. Paladugu, "Implementing Microservices Architecture with Object-Oriented Programming (OOP) and Design Patterns," *International Journal for Multidisciplinary Research (IJFMR)*, vol. 5, no. 2, pp. 1–10, Mar.–Apr. 2023. [Online]. Available: <https://www.ijfmr.com/papers/2023/2/37229.pdf>

[16] O. Puustinen, *GraphQL for Building Microservices*, M.Sc. thesis, Master's Programme in Computer Science, Faculty of Information Technology and Communication Sciences, Tampere University, Tampere, Finland, 2020. Available: <https://trepo.tuni.fi/bitstream/handle/10024/121728/PuustinenOssi.pdf>. [Accessed: Apr. 30, 2025].

[17] J. George, "Optimizing Database Performance in Java and AngularJS Web Applications: Caching and ORM Strategies", 2023. Available: https://www.researchgate.net/profile/Juliana-George/publication/389710439_Optimizing_Database_Performance_in_Java_and_AngularJS_Web_Applications_Caching_and_ORM_Strategies/links/67cf312cd75970006507769c/Optimizing-Database-Performance-in-Java-and-AngularJS-Web-Applications-Caching-and-ORM-Strategies.pdf. [Accessed: Apr. 30, 2025].

Web Services x OOP

GRADEMARK REPORT

FINAL GRADE

80/100

GENERAL COMMENTS

A good piece of work overall - not always written in the most academic style, but coherent and clear.

Good use of mostly academically credible sources.

Well done.

PAGE 1

PAGE 2

PAGE 3

PAGE 4

PAGE 5

PAGE 6

PAGE 7

PAGE 8

PAGE 9

PAGE 10

PAGE 11

PAGE 12

PAGE 13

PAGE 14

PAGE 15

PAGE 16

