

Soundcraft Notepad-8FX

Input Connectors:

- Channel 1: Neutrik XLR/TRS Combo (Switchable Hi-Z)
- Channel 2: Neutrik XLR/TRS Combo
- Channel 3/4: 1/4" Jack L/R (Mono)
- Channel 5/6: RCA L/R



Soundcraft Notepad-8FX

Output Connectors:

- Master: Neutrik XLR L/R
- Aux: 1/4" Jack
- Headphones: 1/4" Jack



Soundcraft Notepad-8FX

- USB Interface: Bi-Directional
- Lexicon Effects: Delay, Chorus, Reverb
- Gain Control: +10dB to +60dB
- Trim Control: -20dB to +20dB Aux/FX
Control: $-\infty$ to +10dB
- Aux Master: $-\infty$ to +10dB
- Level Control: $-\infty$ to +10dB Headphone
Level: 0 to 10dB



Soundcraft Notepad-8FX

EQ Control:

- HF: 12kHz, ± 12 dB
- MF: 2.5kHz, ± 12 dB
- LF: 80Hz, ± 12 dB

Signal Indicators: 4-Segment LED (-20dB, 0dB, +6dB, Peak)

Power Supply: 18V DC Power Supply





← INPUT - e.g. Microphone

← GAIN - level of input

← HF - high frequencies

← MF - mid frequencies

← LF - low frequencies

← AUX/FX - auxiliary and effects level

← PAN - move sound output to left or right

← Overall channel levels (0db is a good start point)



XLR



Jack to Jack



Phono to Mini Jack



SM58 - Dynamic Mic
Shure



SE7 - Condenser Mic
sE Electronics



Presonus AIR10



Active Speaker (no amp
required)

