Project ID : Online
Structure element : Wall
Description : Brick and block cavity wall, partial fill, 2.5 ties per m², cavity greater than 125mm
File reference : 1E1324F6E.PCF

Calculated 'U' value = 0.17W/m²K (Calculated in accordance with BS EN ISO 6946:2017)

Condensation risk has been assessed up to and including Level 4 Humidity Class (dwellings with high occupancy) within UK worst case environmental conditions.

Element Description	Element Thickness (mm)	Thermal Conductivity (W/mK)	Thermal Resistance (m²K/W)	Vapour Resistivity (MNs/gm)	Vapour Resistance (MNs/g)	Mass (kg/m²)	Delta U (W/m²K)
Outside surface resistance			0.044			76.38	0.09
BRICKWORK/FACING	102.5	0.770	0.133	42.00	4.31	78.44	0.31
CAV_VOSPACE	50.0	-	0.800	-	0.00	79.62	1.73
KOOLTHERM K108	80.0	0.016	4.444	-	100.00	85.42	0.47
AERATED BLOCK (k-value = 0.16 W/mK) 0.6% Mortar (1350 Dens)	100.0	0.160	0.607	45.00	4.56	87.44	1.73
PLASTER DAB/5 CAVITY, 20.8% Plaster dabs (16.0mm)	16.0	-	0.189	-	0.09	92.44	0.42
PLASTERBOARD	12.5	0.160	0.078	55.00	0.69	92.73	0.19
PLASTER/SKIM	3.0	0.160	0.019	55.00	0.16	92.82	0.04
Inside surface resistance	-	-	0.130	-	-	93.06	0.31

Detailed U-value Calculation Results

Construction includes 3 bridged layers.

Non-bridged layers
- Outside surface resistance 0.040 m²K/W
- BRICKWORK/FACING 0.133 m²K/W
- CAV_VOSPACE 0.800 m²K/W
- KOOLTHERM K108 4.444 m²K/W
- PLASTERBOARD 0.078 m²K/W
- PLASTER/SKIM 0.019 m²K/W
- Inside surface resistance 0.130 m²K/W

Resistance of non-bridged layers, R_{nb}= 5.682 m²K/W

Detailed U-value Calculation Results (continued)

Resistance of heat flow paths
R_{p1} = R_{nb} + R_{b1} = 5.477 + 0.163 = 5.641 m²K/W F_{p1} = 91.137%
R_{p2} = R_{nb} + R_{b2} = 5.477 + 0.192 = 5.813 m²K/W F_{p2} = 8.823%

Fraction of flow area of materials
TIMBER BATTEN CAVITY, U/V, F_v = 91.1%
Timber batten cavity, U/V, 50mm ctrs + 1% for noggins + loft hatches, F_{ag} = 0.6%

Upper resistance limit
R_{upper} = 1 / (F_{p1}/R_{p1} + F_{p2}/R_{p2})
R_{upper} = 1 / (0.91/5.641 + 0.088/5.813) = 5.663m²K/W

Lower resistance limit
R_{lower} = R_{nb} + R_{b1} / (F_{p1}/F_{p2}/R_{p2})
R_{lower} = 5.477 + 1 / (0.911/170.1633) = (0.888/20.1923) = 5.583 m²K/W

Total resistance of roof
R_t = (R_{upper} + R_{lower}) / 2 = (5.663 + 5.583) / 2 = 5.623 m²K/W

(Correction for mechanical fasteners, Delta U1 = 0.0000W/m²K | Correction for air gaps, Delta Ug = 0.0080W/m²K)
(Alpha 0.0 m^-1 | Fasteners per square metre 0.0000)
(Fasteners cross-sectional area 0.000 mm² | Thermal conductivity of fastener 0.00 W/mK)

(Delta Uf + Delta Ug) is less than 3% of (1 / R) so U = (1 / R) = 0.18W/m²K

For further information on the specified products, e.g. literature or specification clauses, please follows the links below:-

Thermaroof TR27 LPC / PI

Whilst the information and/or specification contained herein is to the best of our knowledge true and accurate we specifically exclude any liability for errors, omissions or otherwise arising therefrom. Details, practices, principles, values and calculations should be verified as to accuracy and suitability for the required purpose for use.

FabCalc 2.0bd © Kingspan Insulation Ltd Aug 2020 Page 2 of 2 IG1844BB.PDF

Project ID : Online
Structure element : Roof - Pitched
Description : Flat roof - bonded
File reference : 1217A7458B1.PCF

Calculated 'U' value = 0.18W/m²K (Calculated in accordance with BS EN ISO 6946:2017)

Condensation risk has been assessed up to and including Level 4 Humidity Class (dwellings with high occupancy) within UK worst case environmental conditions.

Element Description	Element Thickness (mm)	Thermal Conductivity (W/mK)	Thermal Resistance (m²K/W)	Vapour Resistivity (MNs/gm)	Vapour Resistance (MNs/g)	Mass (kg/m²)	Delta U (W/m²K)
Outside surface resistance			0.044			0.170	0.09
BRITMETAL ROOFING 3 LAYERS	8.0	0.230	0.035	0.00	0.00	0.170	0.10
KINGSPAN THERMATCH TR27	120.0	0.024	5.000	360.00	36.00	15.170	3.00
VAPOUR CHECK BITUMINOUS	3.0	0.230	0.013	0.00	0.00	17.420	0.03
BAND: CEMENT SCREED	50.0	1.400	0.036	150.00	7.50	17.815	0.10
CONCRETE 12:4 200# kg/m³	150.0	1.400	0.107	150.00	22.50	20.915	0.25
TIMBER BATTEN CAVITY, U/V, 0.6% roof timber - 47mm @ 500mm ctrs + 1% for noggins + loft hatches (22.0mm)	25.0	-	0.163	-	-	21.440	0.44
PLASTERBOARD	12.5	0.160	0.078	50.00	0.63	21.715	0.19
PLASTER SKIM	3.0	0.160	0.019	50.00	0.15	21.802	0.04
Inside surface resistance	-	-	0.100	-	-	21.972	0.23

Detailed U-value Calculation Results

Construction includes 1 bridged layer.

Non-bridged layers
- Outside surface resistance 0.040 m²K/W
- BRITMETAL ROOFING 0.035 m²K/W
- KINGSPAN THERMATCH TR27 5.000 m²K/W
- VAPOUR CHECK BITUMINOUS 0.013 m²K/W
- BAND: CEMENT SCREED 0.036 m²K/W
- CONCRETE 12:4 200# kg/m³ 0.107 m²K/W
- PLASTERBOARD 0.078 m²K/W
- PLASTER SKIM 0.019 m²K/W
- Inside surface resistance 0.100 m²K/W

Resistance of non-bridged layers, R_{nb}= 5.431 m²K/W

Not all insulation thicknesses shown may currently be stocked, so please check with Kingspan Insulation Customer Service Department on 01544 387601.

Whilst the information and/or specification contained herein is to the best of our knowledge true and accurate we specifically exclude any liability for errors, omissions or otherwise arising therefrom. Details, practices, principles, values and calculations should be verified as to accuracy and suitability for the required purpose for use.

FabCalc 2.0bd © Kingspan Insulation Ltd May 2020 Page 1 of 2 1217A7458B1.PCF

Project ID : Online
Structure element : Wall
Description : Brick and block cavity wall, partial fill, 2.5 ties per m², cavity greater than 125mm
File reference : 1E1324F6E.PCF

Calculated 'U' value = 0.17W/m²K (Calculated in accordance with BS EN ISO 6946:2017)

Condensation risk has been assessed up to and including Level 4 Humidity Class (dwellings with high occupancy) within UK worst case environmental conditions.

Element Description	Element Thickness (mm)	Thermal Conductivity (W/mK)	Thermal Resistance (m²K/W)	Vapour Resistivity (MNs/gm)	Vapour Resistance (MNs/g)	Mass (kg/m²)	Delta U (W/m²K)
Outside surface resistance			0.044			76.38	0.09
BRICKWORK/FACING	102.5	0.770	0.133	42.00	4.31	78.44	0.31
CAV_VOSPACE	50.0	-	0.800	-	0.00	79.62	1.73
KOOLTHERM K108	80.0	0.016	4.444	-	100.00	85.42	0.47
AERATED BLOCK (k-value = 0.16 W/mK) 0.6% Mortar (1350 Dens)	100.0	0.160	0.607	45.00	4.56	87.44	1.73
PLASTER DAB/5 CAVITY, 20.8% Plaster dabs (16.0mm)	16.0	-	0.189	-	0.09	92.44	0.42
PLASTERBOARD	12.5	0.160	0.078	55.00	0.69	92.73	0.19
PLASTER/SKIM	3.0	0.160	0.019	55.00	0.16	92.82	0.04
Inside surface resistance	-	-	0.130	-	-	93.06	0.31

Detailed U-value Calculation Results

Construction includes 3 bridged layers.

Non-bridged layers
- Outside surface resistance 0.040 m²K/W
- BRICKWORK/FACING 0.133 m²K/W
- CAV_VOSPACE 0.800 m²K/W
- KOOLTHERM K108 4.444 m²K/W
- PLASTERBOARD 0.078 m²K/W
- PLASTER/SKIM 0.019 m²K/W
- Inside surface resistance 0.130 m²K/W

Resistance of non-bridged layers, R_{nb}= 5.682 m²K/W

Detailed U-value Calculation Results (continued)

Resistance of heat flow paths
R_{p1} = R_{nb} + R_{b1} = 5.495 + 0.847 = 6.342 m²K/W F_{p1} = 74.745%
R_{p2} = R_{nb} + R_{b2} = 5.495 + 2.153 = 7.648 m²K/W F_{p2} = 6.264%
R_{p3} = R_{nb} + R_{b3} = 5.495 + 0.709 = 6.204 m²K/W F_{p3} = 18.991%
R_{p4} = R_{nb} + R_{b4} = 5.495 + 0.149 = 5.644 m²K/W F_{p4} = 1.314%

Fraction of flow area of materials
BRICKWORK/FACING, F_v = 93.3%
Mortar, F_m = 6.7%
AERATED BLOCK (k-value = 0.15 W/mK), F_v = 80.6%
Mortar, F_m = 20.0%

Fraction of face area of heat flow paths
F_{p1} = F_v . F_v = 0.747
F_{p2} = F_v . F_m = 0.187
F_{p3} = F_m . F_v = 0.055
F_{p4} = F_m . F_m = 0.013

Upper resistance limit
R_{upper} = 1 / (F_{p1}/R_{p1} + F_{p2}/R_{p2} + F_{p3}/R_{p3} + F_{p4}/R_{p4})
R_{upper} = 1 / (0.747/6.342) + (0.0535.765) + (0.1875.187) + (0.0135.644)) = 1 / (0.1125.641) = 6.275m²K/W

Lower resistance limit
R_{lower} = R_{nb} + 1 / (F_{p1}/R_{p1} + F_{p2}/R_{p2} + F_{p3}/R_{p3} + F_{p4}/R_{p4})) = 1 / (F_{p1}/R_{p1} + F_{p2}/R_{p2} + F_{p3}/R_{p3} + F_{p4}/R_{p4})):
R_{lower} = 5.495 + 1 / (0.933/6.5667) + (0.066/70.1136) + 1 / (0.0066/0.1804) + (0.0003/0.0349)) = 1 / (0.0330/0.9900) + 1 / (0.0330/0.9900) + 1 / (0.0330/0.9900) + 1 / (0.0330/0.9900) = 6.667 m²K/W

Total resistance of wall
R_t = (R_{upper} + R_{lower}) / 2 = (6.273 + 6.690) / 2 = 6.185 m²K/W

(Correction for mechanical fasteners, Delta U1 = 0.0849W/m²K | Correction for air gaps, Delta Ug = 0.0000W/m²K)
(Alpha 0.0 m^-1 | Fasteners per square metre 3.5000)
(Fasteners cross-sectional area 23.400 mm² | Thermal conductivity of fastener 17.00 W/mK)

(Delta Uf + Delta Ug) is less than 3% of (1 / R) so U = (1 / R) = 0.1616W/m²K

Not all insulation thicknesses shown may currently be stocked, so please check with Kingspan Insulation Customer Service Department on 01544 387601.

Whilst the information and/or specification contained herein is to the best of our knowledge true and accurate we specifically exclude any liability for errors, omissions or otherwise arising therefrom. Details, practices, principles, values and calculations should be verified as to accuracy and suitability for the required purpose for use.

FabCalc 2.0bd © Kingspan Insulation Ltd Oct 2019 IG1922HB1527

Project ID : Online
Structure element : Solid Ground floor
Description : Solid ground floor (insulation beneath screed / concrete slab)
File reference : 1101250E039.PCF

Calculated 'U' value = 0.18W/m²K (Calculated in accordance with BS EN ISO 13370:2007)

Condensation risk has been assessed up to and including Level 4 Humidity Class (dwellings with high occupancy) within UK worst case environmental conditions.

Element Description	Element Thickness (mm)	Thermal Conductivity (W/mK)	Thermal Resistance (m²K/W)	Mass (kg/m²)	Delta U (W/m²K)
Inside surface				0.170	52.75	0.41
BAND: CEMENT SCREED	65.0	1.400	0.046	92.20	0.22
POLYTHENE SEPARATION LAYER	0.5		0.001	93.12	0.03
KOOLTHERM K103	50.0	0.018	2.778	93.51	1.20
CONCRETE: 1:2:4 200# kg/m³	150.0	1.400	0.107	19.66	0.51
DAMP PROOF MEMBRANE	0.9		0.001	19.80	0.02
Ground	-	-	0.040	79.30	0.18

Ground Floor Details

Calculation method : Perimeter / Area (As defined in BRE IP 1/06)
Perimeter : 0.00m
Area : 0.00m²
Height : 0.00m
Floor type : Solid floor
Earth conductivity : 2.000W/mK
Soil type : Sand or Gravel

Detailed U-value Calculation Results

Total resistance of solid ground floor
R_t = (R_{upper} + R_{lower}) / 2 = (3.143 + 3.143) / 2 = 3.143 m²K/W

(Correction for mechanical fasteners, Delta U1 = 0.0000W/m²K | Correction for air gaps, Delta Ug = 0.0000W/m²K)
(Alpha 0.0 m^-1 | Fasteners per square metre 0.0000)
(Fasteners cross-sectional area 0.000 mm² | Thermal conductivity of fastener 0.00 W/mK)

(Delta Uf + Delta Ug) is less than 3% of (1 / R) so U = (1 / R) = 0.18W/m²K

Not all insulation thicknesses shown may currently be stocked, so please check with Kingspan Insulation Customer Service Department on 01544 387601.

Whilst the information and/or specification contained herein is to the best of our knowledge true and accurate we specifically exclude any liability for errors, omissions or otherwise arising therefrom. Details, practices, principles, values and calculations should be verified as to accuracy and suitability for the required purpose for use.

FabCalc 2.0bd © Kingspan Insulation Ltd May 2016 IG1906285F.FCF

Rev	Description	Date

CODE	SUITABILITY DESCRIPTION
STATUS	PURPOSE OF ISSUE

AUTODESK.
www.autodesk.com/revit

PROJECT
Student Accomodation

TITLE
U-value certification

CLIENT
Owner

DRAWN BY	CHECKED BY	DATE
Aidan Smith	Checker	26/04/21
SCALE (@ A1)	PROJECT NUMBER	
	1	

DRAWING NUMBER	REV
A104	

24/04/2021 18:07:36