

University of Wales Trinity Saint David

Wales Institute of Science & Art



Prifysgol Cymru
Y Drindod Dewi Sant
University of Wales
Trinity Saint David

UWSTD Vehicle Assessment
Body and White Structures (ACHA7004)

Anthony Yin Wai Hau

1550559

08/04/2026

1.Contents

1. Contents.....	2
2. Introduction	3
3. Original Road Vehicle BIW Design.....	4
4. Race Vehicle Modifications	4
5. Stiffness	7
6. NVH	9
7. Materials, Manufacturing and Joining Techniques	10
8. Safety and Comfort	11
9. Regulations	13
10. Conclusion.....	14
11. References	15

Abbreviations

BIW — Body in White

WSC — WSC Group

TCR — Touring Car Racing

OEM — Original Equipment Manufacturer

NVH — Noise, Vibration and Harshness

FIA — Fédération Internationale de l'Automobile

EU — European Union

CAD — Computer-Aided Design

2. Introduction

The Seat Leon TCR provides a BIW case study because it shows how a production road car can be converted into a competition vehicle through selective structural modification. In road form, the Seat Leon had to balance stiffness, crashworthiness, refinement, comfort, durability, manufacturability and cost. In TCR form, those priorities shift toward stiffness, race safety, weight reduction and dynamic response. (WSC Group, n.d.)



Figure 1 Seat Leon TCR assessment vehicle in the UWTSD workshop

This report critically appraises the original road-car BIW and the TCR conversion in terms of stiffness, NVH, materials, manufacturing, joining techniques, safety, comfort and regulations. Its aim is not to argue that the race shell is simply better, but to show how BIW priorities change when motorsport performance and safety take precedence over everyday usability. The assessment draws on workshop observation, technical manuals, FIA/TCR regulations and secondary BIW literature. Without OEM CAD, torsional-rigidity data, a weld schedule or a material-grade map, the analysis remains inferential and limited to directional judgements rather than exact magnitudes.

Methodologically, the shell was assessed through structured visual inspection and comparative engineering judgement, not direct test data. Road-car and TCR configurations were compared using observable workshop BIW features—load paths, cage tie-in points, turret bracing, seat and harness mountings, door structures, removed trim, welded seams and mounting compliance—and interpreted against BIW theory, repair manuals, Cup Racer documentation and FIA/TCR

regulations. Without OEM CAD, a steel-grade map, weld schedule or torsional/modal measurements, conclusions were limited to directional judgements rather than absolute values.

3. Original Road Vehicle BIW Design

The original Seat Leon used a unitary, or unibody, BIW in which the bodyshell and floor acted as the primary load-bearing structure rather than sitting on a separate chassis. In road form, that shell had to balance stiffness, crash protection, NVH refinement, durability, packaging, manufacturability and cost, so it was engineered as a compromise rather than for any single objective. (SEAT, n.d.)

Structurally, the body worked as an integrated load path through the floorpan, sills, pillars, roof rails, bulkhead, cross-members and suspension mounting regions. The front structure had to absorb crash energy while reacting steering and suspension loads, while the side structure and roof protected the passenger cell. This is typical of a modern steel unibody, where stiffness, crashworthiness and mass efficiency must be achieved together. (Brown, Robertson, & Serpento, 2002)

The road-going Leon was also tuned for refinement. Compliant bushes and mountings, intact inner skins and refinement-focused detailing helped suppress noise and vibration, which is consistent with the observed 1440 kg kerb mass and the retention of full production hardware. The shell was therefore not optimised for maximum stiffness or minimum mass, but for balanced road use. (Seat Leon TCR, workshop briefing and vehicle observation, April 2026, 2026)

In manufacturing terms, the BIW was based mainly on stamped steel pressings joined by high-volume resistance spot welding. Panels would typically be positioned in fixtures and assembled through repeatable automated operations, then sealed and corrosion-protected for durability and NVH control. This was a practical road-car solution, not one intended for the narrower demands of motorsport. This road-car strategy was justified by repeatability and refinement; a lighter alternative would likely have increased cost and worsened NVH.

4. Race Vehicle Modifications

Although the Seat Leon TCR appears very different from the road car, its BIW remained closely tied to the production shell because TCR rules required a fundamentally production-based vehicle. The conversion was therefore a selective re-engineering exercise rather than a clean-sheet redesign. (WSC Group, n.d.)

The main structural change was the addition of an FIA-compliant rollover protection system. This added a tubular secondary structure, reinforced footplates, turret triangulation and local reinforcement plates, while selected seams were welded to improve load spreading and joint integrity. Welding and grinding for footplate

installation may disturb original coatings; where dissimilar metals are present, galvanic corrosion may also arise.




Figure 2 Roll-cage footplate at the bodyshell mounting point

Compliance was reduced further by replacing rubber powertrain mountings with solid mounts and by making suspension joints and top mounts much more rigid. These changes reduced wind-up and compliance, improving response but worsening comfort and refinement.

A local front-end support was modified for the race intercooler, with only a minor BIW effect.

Weight reduction was also important. Inner skin material was removed where permitted, and sound deadening, trim and carpeting were stripped out. Despite the added cage and reinforcement, overall mass still fell from about 1440 kg to roughly 1230 kg with fuel, or 1196.25 kg dry. That is about 14.6% in running condition and 16.9% dry, changing inertia and helping explain why stiffness, mounting rigidity and chassis response become more valuable in the race application.

The Leon TCR was not re-engineered as a blank-sheet race chassis, but as a constrained production-shell optimisation. The conversion combined local mass

addition through the cage and reinforcement with broader mass reduction through stripping and selective lightweighting. Cup Racer data support that interpretation: a 1984 cc turbocharged engine producing 242 kW and 410 Nm is packaged within a shell that remains production-derived, while race mass falls enough to change the vehicle's dynamic priorities. That approach was justified by TCR rules; a bespoke chassis might have delivered more freedom, but not within this production-based category.

Table 1 Comparative summary of road-car and TCR BIW characteristics

Aspect	Road-going Seat Leon BIW	Seat Leon TCR / Cup Racer BIW
Core architecture	Steel unibody for crash, NVH, comfort, durability and cost.	Production shell retained, then reinforced and stiffened for racing.
Regulatory basis	EU road type approval and everyday-use requirements.	TCR + FIA rules via the Technical Form and Appendix J.
Mass	Observed road form: ~1440 kg.	Observed race form: ~1230 kg with fuel, ~1196.25 kg dry.
Published race mass	Not stated here for the road shell.	Cup Racer manual: 1150 kg without fuel; later weights vary by version and BoP.
Engine / drivetrain	Production road-car configuration.	1984 cc turbo petrol, 242 kW, 410 Nm, front-wheel drive.
Weight distribution	Not stated.	Published balance: 63.2% front / 36.8% rear.
Materials	Predominantly stamped steel BIW.	Main shell largely steel, with selected carbon, fibreglass and plastic parts.
Joining strategy	High-volume BIW methods, mainly resistance spot welding.	Local seam welding, reinforcement plates and FIA cage integration.
Occupant protection	Airbags, 3-point belts, trim and road comfort systems.	FIA-style seat/harness system, cage, padding and survival-cell logic.

Table 2 Comparative engineering effects of converting the road-going Leon into TCR form

Parameter	Road-car baseline	TCR conversion effect	Engineering consequence
Stiffness	Openings, compliant mounts and comfort-led joints balanced against cost and crash requirements.	Cage tie-ins, turret bracing and local seam welding increase structural continuity.	Lower shell deflection improves alignment control and steering repeatability.
NVH	Bushes, trim, damping layers and elastomeric mounts isolate vibration.	Rigid mounts, spherical joints and stripped trim reduce isolation and damping.	More structure-borne vibration, noise and harshness reach the occupant cell.
Safety philosophy	Road restraint system integrates belts, airbags, trim and public-road usability.	Cage, harnesses, reinforced anchorages and side-impact bars prioritise driver survival in racing.	Motorsport protection improves, but everyday accessibility and restraint logic worsen.
Mass / inertia	Higher kerb mass with full trim, sound deadening and production hardware.	Selective lightweighting offsets cage mass and reduces running mass.	Lower inertia improves transient response, braking and acceleration sensitivity.
Compliance / mounting	Rubber mountings and compliant joints filter load transmission.	Solid powertrain mounts and stiffer joints reduce relative movement between systems and shell.	Sharper chassis response is gained at the cost of isolation and comfort.

5. Stiffness

Stiffness is one of the clearest ways in which the Leon changes character from road car to race car. In the production vehicle, the BIW had to deliver adequate bending and torsional stiffness while still coexisting with crash deformation, NVH refinement, manufacturability and cost. In TCR form, stiffness becomes a higher priority because bodyshell deflection affects steering precision, suspension consistency and chassis response.

The largest stiffness gain comes from the cage and its triangulated load paths through the occupant cell. The cage creates stiffer, more continuous load paths between the sills, pillars, roof structure and suspension pick-up regions, reducing relative displacement under cornering, braking and kerb-strike loads. By tying the turrets, roof hoop, pillars and sill regions into a more closed structural loop, the conversion reduces aperture shear deformation and increases resistance to torsional twist. Bracing to suspension mounting regions, reinforcement plating and local seam

welding further reduce flex at key mounting points. As shown in Figure 3, the cage acts as a secondary tubular structure integrated with the production bodyshell.



Figure 3 Overall roll-cage layout showing integration with the production-based bodyshell




Figure 4 Rear left suspension turret area with cage tie-in and local reinforcement

Further gains arise from the removal of compliant mounting systems. Solid drivetrain mounts and stiffer suspension joints reduce elastic movement between the mechanical systems and the BIW, making the car feel more immediate in response, although lightweighting in non-critical closures may slightly reduce local panel stiffness. (Seat Leon TCR, workshop briefing and vehicle observation, April 2026, 2026)

No direct torsional-rigidity or modal test data were available, so the exact increase cannot be quantified, but the direction of change is still supported by cage geometry, seam welding, reinforced mounting regions and reduced mounting compliance. Supplementary views are provided in Appendix A. (Brown, Robertson, & Serpento, 2002; Fedotova, 2020; Seat Leon TCR, workshop briefing and vehicle observation, April 2026, 2026) Although the complete race car is lighter, the modified BIW includes local mass additions from the cage, footplates, seam welding and reinforcement plates, so the overall weight reduction comes mainly from removing non-structural production components.

6.NVH

In contrast to stiffness, the NVH characteristics of the Seat Leon are significantly compromised by the race conversion. In the road car, NVH control formed a central BIW objective and depended on compliant mountings, bushes, sound-deadening materials, trim and intact closure inner skins.

The TCR conversion removes or weakens many of those controls. Solid metal powertrain mounts, spherical bearings, rigid suspension joints and solid top mounts reduce isolation and damping, so more excitation from the engine, driveline and road surface is transmitted directly into the bodyshell as structure-borne vibration. In that sense, the same reduction in compliance that improves response also predictably worsens refinement.



Figure 5 Solid engine mount replacing the compliant production mounting

Additional deterioration comes from stripping sound-deadening materials, carpets and trim, together with the lightweighting of closure inner skins. The cage also changes modal behaviour and creates new vibration paths. Removing damping layers and cavity trim reduces panel damping, so more high-frequency content is radiated into the cabin. The harsher cabin is therefore a predictable result of removing compliance and damping from the system. (Brown, Robertson, & Serpento, 2002; Hafizi, 2017) In racing that compromise is justified; retaining softer mounts would have improved refinement but reduced response precision.

7. Materials, Manufacturing and Joining Techniques

The material strategy of the Leon TCR is selective. The main BIW shell remains steel, while lighter carbon, fibreglass and plastic components are used mainly in secondary areas such as bumper assemblies, ducts, covers and other removable body panels rather than the core load-bearing shell. It does not attempt a full BIW lightweight re-architecture because TCR rules, cost, repair practicality and the retained production shell favour a more conservative solution. (SEAT Sport, 2015; FIA/WSC, 2026) Keeping the primary shell in steel is justified; a wider aluminium/composite redesign might cut mass, but would complicate joining, repair and cost.

This approach is also defensible in manufacturing terms. Steel remains dominant in BIW design because it offers a strong balance of cost, formability, joining familiarity and crash performance, especially when advanced high-strength steels are used to improve efficiency without abandoning established press and weld processes. The Leon TCR therefore reflects a rational compromise rather than a radical material departure. (Hu & Feng, 2021)

The same logic applies to joining. Production BIWs rely on fast, repeatable methods such as resistance spot welding, whereas the race conversion accepts slower, more localised seam welding and reinforcement plating for better load-path continuity and mounting stiffness. Figure 6 shows an example of the additional local seam welding and reinforcement used in the race conversion, illustrating the shift from production spot welding to more localised stiffness-focused modification. (Groover, 2017; Nadimi, Pouranvari, Ansari, & Pouranvari, 2023; FIA/WSC, 2026)




Figure 6 Seam-welded centre tunnel and local reinforcement in the modified BIW

8. Safety and Comfort

Converting the Leon to TCR form changed both safety philosophy and occupant comfort. In road form, safety was designed for public-road use and combined structural protection with seat belts, airbags, crash sensors and interior systems that supported everyday usability. (Seat Leon 2013 – Leon ST 2013 – Body Repair Manual, 2023)

In TCR form, safety shifts toward occupant survival in high-energy motorsport accidents. The cage, reinforced footplates, turret bracing, side-impact bars and stronger seat and harness mountings create a rigid protective cell. Instead of airbags and conventional road restraints, the driver is kept within that structure by a racing seat and harness.

Comfort is reduced accordingly. The removal of refinement systems, together with rigid seating, harnesses and solid mountings, creates a far harsher cabin. The TCR conversion improves safety in the motorsport context, but at the expense of the restraint strategy, accessibility and comfort expected of a road car. This is justified for circuit accidents; a road-car restraint philosophy would improve usability but offer less secure retention within the cage-protected cell.



Figure 7 Rear door structure showing local modification and lightweighting for race use



Figure 8 Racing seat, harness and cage members within the modified occupant cell

9. Regulations

The regulatory environment changed fundamentally between the road-going Leon and the TCR car. In road form, the original Leon sat within the EU whole-vehicle type-approval framework centred on Directive 2007/46/EC, so the BIW had to operate within a broader legal system covering crashworthiness, restraint integration, noise, emissions and general road usability. The bodyshell was judged not only on stiffness or survival-cell strength, but also on how it integrated airbags, seat belts, doors, trim and visibility systems. (European Parliament and Council, 2007)

In race form, those priorities are replaced by the TCR and FIA rule set. TCR regulations require front-wheel drive, a mass-produced 4/5-door car of at least 4.2 m in length, and a single-turbo petrol engine of 1750–2000 cm³. They also restrict how far the production shell can be modified. This is why the Leon TCR remains production-based rather than becoming a bespoke tube-frame race car. (FIA/WSC, 2026)

FIA Appendix J makes the safety implications more specific. The safety cage is compulsory; occupants must remain within its volume; homologated or certified cages cannot be modified; seats must be FIA-approved; and for circuit competition window nets are mandatory. Harness anchorage points must also meet defined structural requirements, including reinforced steel plates on the shell. (FIA, 2026)

Regulation did not merely limit the design; it shaped the engineering logic of the final car. Road approval required a broad public-use optimisation, whereas the TCR and FIA rules narrowed the problem to production-based competition performance and driver protection. The result is a shell that is more rigid and protective in motorsport terms, but less refined and less broadly optimised than the road-going vehicle from which it derives. (European Parliament and Council, 2007; FIA, 2026; FIA/WSC, 2026) That restriction is justified by category control; a freer ruleset could permit a lighter, stiffer bespoke shell, but at higher cost and with less production relevance.

A limitation of this appraisal is that no OEM BIW CAD model, material grade map, weld schedule, homologation drawings or measured torsional/modal test data were available. Exact rigidity, joint stiffness, mode shapes and steel-grade distribution could therefore not be verified directly. Published race-car mass values also vary by version and rule set. The discussion should therefore be read as a triangulated engineering assessment based on workshop observation, technical manuals, regulations and BIW literature rather than as a full homologation-level audit. (SEAT Sport, 2015; FIA/WSC, 2026)

The conversion shifts the Leon from a type-approved road vehicle to a competition-only vehicle with a different safety logic. In road form, the BIW formed part of an approval package including seats, belts, airbags, trim and door systems for normal traffic use. Once converted to TCR form, that basis is compromised because the restraint strategy, seating, interior fit-out and usability assumptions are no longer those of the certified road vehicle. A welded-in cage, racing seat and harnesses improve motorsport protection, but replace one regulated safety concept with another.

10. Conclusion

The Seat Leon TCR shows that BIW engineering is about managing trade-offs rather than making a structure universally stronger, lighter or stiffer. In road form, the Leon BIW represented a broad optimisation across crashworthiness, NVH, comfort, durability, manufacturability and cost. In TCR form, the same shell was selectively re-prioritised so that stiffness, driver protection and dynamic response took precedence over refinement, accessibility and everyday usability. The comparison therefore shows that the road shell suits a multi-objective public-road brief, whereas the TCR shell suits a tightly constrained motorsport brief.

Neither shell is superior in every respect because each is justified by a different operating environment and design brief.

11. References

- ACEA. (2023). *The Automotive Regulatory Guide*. European Automobile Manufacturers' Association.
- Brown, J., Robertson, A., & Serpento, S. (2002). *Motor Vehicle Structures: Concepts and Fundamentals*. Oxford: Butterworth-Heinemann.
- European Parliament and Council. (2007). *Directive 2007/46/EC of the European Parliament and of the Council of 5 September 2007 establishing a framework for the approval of motor vehicles and their trailers, and of systems, components and separate technical units intended for such vehicles*. EUR-Lex. Retrieved from <https://eur-lex.europa.eu/LexUriServ/LexUriServ.do?uri=CONSLEG:2007L0046:20120226:EN:PDF>
- Fedotova, O. (2020). BIW structure development in accordance with passive safety requirements using several optimization methods. *IOP Conference Series: Materials Science and Engineering*, 986, 012057.
- FIA. (2026). *Appendix J – Article 253*.
- FIA. (n.d.). *Regulations*. Retrieved from <https://www.fia.com/regulation/category/123>
- FIA/WSC. (2026). *FIA TCR World Tour Technical Regulations*.
- Groover, M. (2017). *Groover's Principles of Modern Manufacturing: Materials, Processes, and Systems* (6 ed.). Wiley.
- Hafizi, Z. (2017). Modal properties investigation of car body-in-white with attached windscreen and rear screen. *IOP Conference Series: Materials Science and Engineering*, 257, 012038.
- Hu, X., & Feng, Z. (2021). *Advanced High-Strength Steel—Basics and Applications in the Automotive Industry*. ORNL/TM-2021/2047.
- Jenny, M. (2023). Advantages and Challenges of Implementing Lightweight Materials in Automobiles: A Review. *International Journal of Scientific and Research Publications*, 13(9).
- Modular toolkit strategy as recipe for success: the MQB celebrates tenth anniversary*. (2022). Retrieved from <https://www.volkswagen-newsroom.com/en/press-releases/modular-toolkit-strategy-as-recipe-for-success-the-mqb-celebrates-tenth-anniversary-8030>
- Nadimi, N., Pouranvari, M., Ansari, R., & Pouranvari, M. (2023). Understanding fusion zone hardness in resistance spot welds for advanced high strength

steels: Strengthening mechanisms and data-driven modeling. *Journal of Materials Research and Technology*, 5549–5565.

Papa, I., Panico, M., Carandente, M., & Lopresto, V. (2024). Innovative joining technologies for lightweight material vehicles. *Proceedings of the Institution of Mechanical Engineers, Part C: Journal of Mechanical Engineering Science*.

SEAT. (n.d.). *Bodywork Construction of the Car – Car Terms*. Retrieved from <https://www.seat.com/car-terms/b/bodywork-construction>

Seat Leon 2013 – Body Repairs. (2023). Retrieved from <https://procarmanuals.com/seat-leon-2013-body-repairs/>

Seat Leon 2013 – Leon ST 2013 – Body Repair Manual. (2023). Retrieved from <https://procarmanuals.com/seat-leon-2013-leon-st-2013-body-repair-manual/>

Seat Leon TCR, workshop briefing and vehicle observation, April 2026. (2026). *UWTSD workshop observation*.

SEAT Sport. (2015). *LEON CUP RACER Technical Manual*.


SEST. (2012, 11 28). *New SEAT Leon and Toledo both awarded five stars by Euro NCAP*. Retrieved from <https://seatmedia.co.uk/assets/documents/original/29848-2012-11-28.doc>

WSC Group. (n.d.). *TCR*. Retrieved from <https://wsc.group/tcr>

12. Appendix A Cage integration views



Appendix Figure A1 Side view of roll-cage integration at the door aperture and sill



Appendix Figure A2 Welded cage joint and attachment plate at the bodyshell

13. Appendix B Additional workshop views

Additional workshop views supporting the front-structure, local mounting and cage-integration discussion.



Appendix Figure B1 Front-end support modified to accommodate the race intercooler package



Appendix Figure B2 Front suspension mounting region of the modified front structure