

Exam 11/05/20 13:00 - 15:00
Advanced Stress Analysis + FEA
(M6X00420)

Sion Evans (P150600) 2/20

Two

b i) $30 \times 10^3 \times 20 \times 10^3 \text{ m}$ Thickness $2.5 \times 10^{-3} \text{ m}$
 $L = 2.4 \text{ m}$ $\sigma = 480 \times 10^6 \text{ Pa}$ $E = 190 \times 10^9$

$$u = \frac{P^2 L}{2AE} = \frac{\sigma^2 AL}{2E}$$

$$A = (25 \times 10^{-3})(15 \times 10^{-3})$$
$$= 3.75 \times 10^{-4} \text{ m}^2$$

$$A = (30 \times 10^{-3})(20 \times 10^{-3}) = 3.75 \times 10^{-4}$$

$$u = \frac{(480 \times 10^6)^2 (2.25 \times 10^{-4})(2.4)}{(2)(190 \times 10^9)}$$

$$= \underline{\underline{2.25 \times 10^{-4} \text{ m}^2}}$$

$$= \underline{\underline{327.41 \text{ J}}}$$

ii) $P.E = mgh$ $u = \frac{P^2 L}{2AE}$ $P.E = u$

$$Mgh = \frac{P^2 L}{2AE}$$

$$P = \sigma A$$

$$Mg = W$$

$$Wh = \frac{\sigma A^2 L}{2AE} = \frac{\sigma AL}{2E}$$

$$AL = V$$

$$h = \frac{\sigma V}{2WE}$$

Exam 11/05/20 13:00 - 15:00
Advanced Stress Analysis + FEA
(M6X00420)

Sion Evans (P150600) 3/20

Two

b iii) $\sigma = \frac{h z w E}{\sqrt{}}$ $M = 20 \text{ kg}$ $h = 450 \times 10^{-3} \text{ m}$

$$\sigma = \frac{(450 \times 10^{-3}) (2) (20) (9.81) (190 \times 10^9)}{(2.25 \times 10^{-4}) (2.4)}$$

$$\sigma = 6.21 \times 10^{16} \text{ Pa}$$

iv) $\sigma_{\max} = 6.21 \times 10^{16}$ $d = 20 \times 10^{-3}$ $L = 2.4$

$$V = \frac{h z w E}{\sigma} = \frac{(450 \times 10^{-3}) (2) (20) (9.81) (190 \times 10^9)}{6.21 \times 10^{16}}$$

$$5.4 \times 10^{-4} = \frac{(\pi d e^2}{4} - \frac{\pi d i^2}{4}) \cdot L = 5.4 \times 10^{-4} \text{ (A)}$$

$$\frac{5.4 \times 10^{-4}}{2.4} = \frac{(\pi) (20 \times 10^{-3})^2}{4} - \frac{\pi d i^2}{4} \quad 0.225 \times 10^{-4} =$$

$$\cancel{2.25 \times 10^{-4}} \quad \frac{\pi d i^2}{4} = \frac{\pi (20 \times 10^{-3})^2}{4} - 2.25 \times 10^{-4}$$

$$d i = \sqrt{\frac{(8.916 \times 10^{-5}) (4)}{\pi}} = 10.65 \times 10^{-3} \text{ m}$$