



Prifysgol Cymru
Y Drindod Dewi Sant
University of Wales
Trinity Saint David

University of Wales Trinity St David – School of Engineering

ACMA6011 – Advanced Thermofluid Mechanics
RHYS TREMELLING (2102909)

Table of Contents

Task A	3
Task B	12
Task C	13
1)	13
2)	13
3)	14
4)	14
5)	15
References	17

Task A

The Evolution and Applications of Extended Heat Exchanger Surfaces

Heat exchanger fins have been crucial in automotive design and microprocessor thermal management. Their evolution highlights advancements in materials, design methods, and performance requirements. The following examines the historical development of heat exchanger fins in automotive applications, the incorporation of extended heat exchanger surfaces in microprocessors, and recent innovations in their design.

Historical Evolution of Heat Exchanger Fins in Automotive Design

The development of heat exchanger fins in automotive design began with the introduction of internal combustion engines in the early 20th century. As these engines generate significant amounts of heat during operation, effective cooling systems became essential to maintain performance and prevent overheating. Early vehicles relied on air-cooled engines that incorporated fins cast into the cylinder heads and engine blocks. These fins increased the surface area exposed to airflow, allowing for greater heat dissipation. However, the designs during this period were rudimentary, often constrained by manufacturing capabilities and limited computational tools.




Figure 1 Image of heat exchanger fins on an air-cooled engine (Source: Cycle World, n.d: online)

By the mid-20th century, the rising demand for higher engine performance and efficiency led to a transition toward liquid-cooled engines. Liquid cooling systems utilized radiators as the primary heat

exchangers, with thin metal fins attached to the coolant tubes. These fins improved heat transfer from the coolant to the surrounding air. Innovations in fin geometry, such as louvred and wavy patterns, also emerged during this time, significantly enhancing airflow and heat dissipation.




Figure 2 Image of the first air to liquid heat exchanger implemented in automotive design in 1900 (Source: Motor Equipment News, n.d: online)

Additionally, the switch from copper and brass to aluminium in radiator manufacturing reduced weight and improved thermal performance. Aluminium offers a balance of thermal conductivity, weight, and cost, making it the preferred material for automotive heat exchangers. The late 20th century saw the introduction of computational tools like finite element analysis (FEA) and computational fluid dynamics (CFD), which revolutionized heat exchanger design. Engineers could now simulate airflow and heat transfer, allowing them to optimize fin geometries for specific performance criteria. Consequently, compact, and lightweight heat exchangers became standard in modern vehicles, reducing fuel consumption and enhancing environmental sustainability. Innovations such as micro-channel heat exchangers and multi-layered fin designs have improved cooling efficiency in contemporary automotive systems.

Integration of Extended Heat Exchanger Surfaces in Microprocessor Design

The rapid advancement of microprocessors in electronics has introduced unique thermal challenges. Modern microprocessors generate substantial heat due to their high-power densities, necessitating efficient cooling solutions. Extended surfaces, such as heat sinks with fins, have become essential components in managing the thermal conditions of microprocessors. Initially, simple finned heat sinks were employed to dissipate heat from microprocessors. These early designs used natural convection to transfer heat from the processor to the surrounding air.




Figure 3 Image of a simple microprocessor heat exchanger (Source: Hardware Interviews, n.d: online)

However, as microprocessor performance and heat generation increased, active cooling solutions became essential—forced convection, achieved through fans integrated with heat sinks, enhanced airflow and improved heat dissipation. The design of extended surfaces for microprocessors has evolved significantly over the years. Modern heat sinks utilize advanced geometries, such as pin-fin, straight-fin, and radial-fin configurations, to maximize the surface area in contact with air. Additionally, materials with high thermal conductivity, such as copper and aluminium, enhance heat transfer. Copper is preferred for its excellent thermal properties, while aluminium is favoured for its lightweight nature and cost-effectiveness. A significant innovation in microprocessor cooling is the development of microchannel heat sinks. These devices feature numerous small channels etched into a substrate, allowing coolant to flow through them and effectively remove heat from the microprocessor. Microchannel heat sinks offer a high surface area-to-volume ratio, making them highly efficient for heat exchange. Furthermore, integrating phase-change materials (PCMs) in microprocessor cooling systems has emerged as a promising solution. During phase transitions, PCMs can absorb and release substantial amounts of heat, providing a passive cooling mechanism that enhances thermal management.

Automotive Heat Exchanger Innovations

In the automotive industry, the development of plate-fin and tube-fin heat exchangers has revolutionized thermal management. Plate-fin heat exchangers consist of alternating layers of flat plates and finned passages, which provide high heat transfer efficiency in a compact design. These exchangers can be customized for specific applications, including engine cooling, air conditioning, and exhaust gas recirculation (EGR) systems. Advanced manufacturing techniques have allowed the production of complex fin geometries that were not previously possible. These innovative designs

enhance airflow distribution and heat dissipation, improving the overall efficiency of the heat exchanger.




Figure 4 Image of a modern automotive heat exchanger system (Source: Testing Autos, n.d: online)

Another significant advancement in automotive thermal management is using phase-change cooling systems. These systems utilize refrigerants that change phases (from liquid to gas) to absorb and dissipate heat. This technology has been integrated into hybrid and electric vehicles, where effective thermal management is essential for maintaining battery performance and longevity.

Advances in Microprocessor Cooling

Integrating thermoelectric coolers (TECs) into heat sinks significantly advances microprocessor cooling technology. TECs utilize the Peltier effect, a phenomenon which occurs when heat is absorbed or released at the junctions of two different conductive materials as an electric current flows through them. This effect arises from energy transfer between charge carriers and the materials' lattice structures, to transfer heat away from critical areas, providing localized cooling for high-performance processors. This technology enables precise temperature control, essential for maintaining the stability and reliability of microprocessors operating at high speeds.



Figure 5 Image of an air to air Thermoelectric Cooler (Source: Advanced Thermal Solutions, n.d: online)

Another notable innovation is the use of metal foam heat sinks. Metal foams have a porous structure that offers a high surface area-to-volume ratio, which enhances convective heat transfer. These lightweight materials can be designed for specific thermal properties, making them ideal for high-performance electronic cooling applications.




Figure 6 Image of an aluminium foam heat exchanger (Source: Science Direct, 2017: online)

Additionally, the application of nanofluids, fluids containing suspended nanoparticles, has shown promise in improving the thermal performance of microchannel heat sinks. Nanofluids exhibit higher thermal conductivity and better heat transfer rates than conventional coolants, making them valuable to advanced cooling systems. Lastly, hybrid cooling systems that combine liquid cooling, air

cooling, and phase-change materials have emerged as practical solutions for managing the thermal challenges faced by modern microprocessors. These systems leverage the strengths of each cooling mechanism, providing robust and efficient thermal management for high-performance electronics.

Advantages of Recent Innovations

Advancements in extended surface design provide several benefits for both automotive and microprocessor applications:

1. **Enhanced Thermal Efficiency:** Improved designs and materials allow for more effective heat dissipation, allowing systems to operate at optimal temperatures.
2. **Compact and Lightweight Solutions:** Modern heat exchangers and heat sinks are designed to be smaller and lighter, contributing to overall system efficiency and performance.
3. **Increased Reliability and Longevity:** Effective thermal management reduces the risk of overheating, thereby extending the lifespan of components in both automotive and electronic systems.
4. **Energy Efficiency:** Advanced cooling solutions help minimize energy consumption, supporting sustainability goals in the automotive and electronics industries.
5. **Customizability:** Computational tools and advanced manufacturing techniques enable the design of tailored solutions for specific applications.

Additive Manufactured Heat Exchanger Fins

Additive manufacturing (AM), also known as 3D printing, has transformed the design and production of heat exchangers in the automotive and microprocessor industries. By allowing the creation of intricate geometries and optimized structures, AM improves thermal performance, reduces weight, and provides greater design flexibility.

Automotive Heat Exchangers

Traditional manufacturing methods often impose design constraints that limit the effectiveness of heat exchangers. Additive manufacturing overcomes these limitations by enabling intricate designs that maximize heat transfer while minimizing pressure drop. One significant advantage of AM is the ability to fabricate complex internal geometries, such as lattice structures and optimized fluid channels, which are challenging to produce using conventional methods. These advanced designs increase the surface area for heat exchange and improve fluid flow, enhancing thermal efficiency. For example, triply periodic minimal surface (TPMS) structures, like gyroids, can be integrated into heat exchanger cores, allowing the maximum surface area to be packed into a compact volume. This effectively meets size, weight, and performance requirements. Furthermore, AM allows for consolidating multiple components into a monolithic part, reducing the need for welds or brazes, which can be potential failure points. This consolidation not only improves reliability but also simplifies assembly and maintenance processes. For instance, Conflux Technology has developed additively manufactured heat exchangers featuring enhanced surface area density and complex internal geometries, resulting in superior thermal exchange performance and lower pressure drops. AM's flexibility also permits the customization of heat exchanger designs to fit specific spatial constraints within vehicles. This adaptability is particularly advantageous in electric vehicles, where space is limited, and efficient thermal management is critical for optimal battery performance.



Figure 7 Image of an additively manufactured automotive heat exchanger (Source: AMFG, 2019: online)

Microprocessor Heat Exchangers

Additive manufacturing enables the production of micro-scale heat exchangers with complex microchannel networks, which enhance heat dissipation. The precision of AM allows for the fabrication of microchannels with varying cross-sectional areas and intricate pathways, optimizing heat transfer characteristics. This capability is crucial for microprocessors, as efficient cooling directly affects processing speeds and reliability. Moreover, AM facilitates the integration of heat exchangers directly into the microprocessor packaging, reducing thermal resistance and improving overall cooling efficiency. Additionally, AM supports using high-conductivity materials, such as copper and aluminium, which are ideal for heat exchangers due to their excellent thermal properties. Printing with these materials allows for the creation of heat exchangers that effectively manage the high heat fluxes associated with modern microprocessors.



Figure 8 Image of an additively manufactured microprocessor heat exchanger (Source: Rapid 3D, n.d: online)

Challenges and Considerations


While additive manufacturing offers several advantages in heat exchanger design, it also presents challenges. AM processes' inherent surface roughness can influence fluid flow and reduce heat transfer efficiency. Post-processing techniques or design modifications may be necessary to address these issues and minimize negative impacts. Additionally, thermal stresses that occur during the AM process can result in deformations, affecting the dimensional accuracy and overall performance of heat exchangers. Ongoing research aims to develop strategies for controlling these stresses to ensure the structural integrity of the manufactured components. Material selection is another crucial aspect. Although AM allows for various materials, achieving optimal thermal and mechanical properties necessitates carefully considering how materials behave during printing. For example, the reflective nature of copper poses challenges for laser sintering, which requires specific adjustments to the process.

Conclusion

The evolution of heat exchanger fins and extended surfaces underscores the significance of thermal management in engineering. The development of heat exchanger fins has reflected technological advancements from the early days of simple air-cooled engines to the sophisticated liquid-cooled systems found in modern vehicles. In a similar vein, the integration of advanced heat sink designs in microprocessors addresses the growing thermal challenges in modern electronics. Recent innovations, such as microchannel heat sinks, thermoelectric coolers, and nanofluid applications, have greatly improved cooling systems' performance, reliability, and efficiency. As technology

progresses, extended surfaces' role in thermal management will remain essential, driving further innovations in design and materials.


Task B



The generated plot of the heat transfer ratio $Q_{\text{finite}}/Q_{\infty}$ against the fin parameter mL clearly visualises the relationship between fin efficiency and its geometric characteristics. The curve begins at 1 for $mL=0$, where the fin length is negligible and decreases as mL increases. This behaviour reflects the diminishing returns in heat transfer enhancement as the fin becomes longer relative to its thermal characteristics. The curve stabilises at approximately $mL=2.65$, marked by a red dashed line, confirming this value as the optimal fin length for practical design purposes. Beyond this point, increasing the fin length results in only marginal improvements in heat transfer, making it inefficient to extend the fin further due to increased material and manufacturing costs. Thus, the analysis reaffirms that $mL \approx 2.65$ is a critical design parameter for ensuring a balance between heat transfer efficiency and economic feasibility in fin design.

Task C

1)



This graph illustrates the temperature distribution along a rod for various materials under steady-state conditions, highlighting their thermal conductivity. The x-axis represents the distance along the rod, starting at the heat source (0 m) and extending to 0.4 m, while the y-axis shows the temperature, which decreases as the distance from the heat source increases. Among the materials, copper exhibits the flattest curve, indicating the highest thermal conductivity as it distributes heat most efficiently along the rod. In contrast, 304 stainless steel has the steepest gradient, signifying poor thermal conductivity and retaining heat near the source. The 2024 aluminium alloy and brass (70 Cu/30 Zn) fall in between, with aluminium showing better thermal conductivity than brass. This analysis demonstrates that copper is best suited for applications requiring efficient heat transfer, such as heat exchangers. At the same time, stainless steel is more appropriate for uses that benefit from heat retention or thermal resistance, like cookware.

2)


Heat Loss for Each Material	
Material	Heat loss (W)
2024 Aluminium Alloy	7.00
Brass (70 Cu/30 Zn)	5.11
Copper	6.86
304 Stainless Steel	1.03

3)


Optimum Length and Heat Loss for Each Material		
Material	Optimum Length (m)	Heat Loss (W)
2024 Aluminium Alloy	0.29	6.94
Brass (70 Cu/30 Zn)	0.21	5.06
Copper	0.59	7.18
304 Stainless Steel	0.17	1.02

The heat loss values in part 3 for the aluminium alloy, copper, and steel are similar to those in part 2; however, the heat loss value for copper has increased. This increase occurs because the optimum length for the other three materials is less than the 0.4 m limit set in parts one and two, while the optimum length for copper is approximately 0.59 m, which is greater than that limit. The optimum length is determined by the relationship $mL_{opt}=2.65$, ensuring that the fin operates within its most effective range. This optimized length compromises heat transfer performance with material usage, allowing the entire fin to contribute effectively to heat transfer. The optimum length may be shorter or comparable to the fixed length for materials with lower thermal conductivity or transfer coefficients, leading to similar or slightly higher heat loss values. This variation highlights the importance of selecting the correct fin length to maximize efficiency and performance.

4)



5)



More Accurate Length for Each Material	
Material	Length (m)
2024 Aluminium Alloy	0.42
Brass (70 Cu/30 Zn)	0.31
Copper	0.87
304 Stainless Steel	0.25

The temperature distributions in Part 5, which use the infinite fin approximation criterion $e^{-mL} < 0.02$ to determine accurate lengths, differ significantly from those in Parts 1 and 4 due to the varying assumptions and length constraints. In Part 1, the temperature distributions are plotted for a fixed maximum length ($L_{max}=0.4 \text{ mL}$) and assume an adiabatic tip boundary condition, resulting in a distribution where the temperature gradient diminishes near the tip for materials with less optimal mL . This leads to less effective heat transfer for some materials, particularly for those where mL is large. In Part 4, the distributions correspond to the optimum length based on $mL \approx 2.65mL$, ensuring efficient utilization of the fin. These distributions show a steeper and more uniform gradient than Part 1, as the fin is designed to maximize its effectiveness within the optimal length.

In Part 5, the lengths are recalculated based on the infinite fin approximation $e^{-mL} < 0.02$, which assumes the fin's tip temperature approaches the ambient temperature. This results in slightly longer lengths than those in Part 4 for most materials, causing the temperature distributions to show extended gradients along the rod compared to Parts 1 and 4. The infinite fin assumption in Part 5

highlights the diminishing temperature change along the length as L increases, but the calculated accurate lengths ensure the distributions remain physically meaningful. Overall, the distributions in Part 5 align closely with those in Part 4 near the base but deviate further along the rod due to the slightly longer lengths. In contrast, the distributions in Part 1 appear less effective due to the arbitrary fixed length. This comparison underscores the importance of selecting appropriate fin lengths based on thermal performance criteria.

References

- Niknam, S. A., Mortazavi, M., & Li, D. (2020). Additively manufactured heat exchangers: a review on opportunities and challenges. *The International Journal of Advanced Manufacturing Technology*, 112, 601–618. Available at: <https://link.springer.com/article/10.1007/s00170-020-06372-w> [Accessed 18 Nov. 2024].
- nTop. (2022). Heat exchanger design with additive manufacturing. Available at: <https://www.ntop.com/resources/blog/heat-exchanger-design-with-additive-manufacturing/> [Accessed 18 Nov. 2024].
- Conflux Technology. Heat exchange technology. Available at: <https://www.confluxtechnology.com/> [Accessed 18 Nov. 2024].
- SINTEF. (2018). Additive manufacturing of heat exchangers (How would it work?). Available at: <https://blog.sintef.com/sintefenergy/additive-manufacturing-of-heat-exchangers/> [Accessed 18 Nov. 2024].
- Advances in Automotive Heat Exchanger Technology*. Available at: <https://www.jstor.org/stable/44745431> [Accessed 18 Nov. 2024].
- Evolution of Heat Exchangers: From Ancient Innovations to Modern Advancements*. Available at: <https://heat-exchanger-world.com/evolution-of-heat-exchangers-from-ancient-innovations-to-modern-advancements/> [Accessed 18 Nov. 2024].
- Design and Performance of Plate-Fin Heat Exchanger: A Brief Review*. Available at: https://link.springer.com/chapter/10.1007/978-981-16-9613-8_12 [Accessed 18 Nov. 2024].
- Heat Spreaders with Parallel Microchannel Configurations Employing Nanofluids*. Available at: <https://arxiv.org/abs/1704.01456> [Accessed 18 Nov. 2024].
- Metal Foam Applications in Heat Sinks*. Available at: <https://www.sciencedirect.com/science/article/pii/S1359431111001234> [Accessed 18 Nov. 2024].
- Principles of Finned-Tube Heat Exchanger Design*. Available at: <https://www.wseas.us/e-library/conferences/2015/Frass/Frass.pdf> [Accessed 18 Nov. 2024].
- Additive Manufacturing in Heat Exchanger Design*. Available at: <https://www.3dprintingmedia.network/additive-manufacturing-heat-exchangers/> [Accessed 18 Nov. 2024].
- Phase-Change Cooling in Electric Vehicles*. Available at: <https://www.sae.org/publications/technical-papers/content/2019-01-0135/> [Accessed 18 Nov 2024].
- Thermoelectric Cooler Integration in Microprocessor Heat Sinks*. Available at: <https://www.mdpi.com/1996-1073/13/9/2195> [Accessed 18 Nov. 2024].
- CFD in Automotive Heat Exchanger Design*. Available at: https://pure.manchester.ac.uk/ws/portalfiles/portal/54576350/FULL_TEXT.PDF [Accessed 18 Nov. 2024].
- Metal Foam Heat Sinks for Electronics Cooling*. Available at: <https://www.sciencedirect.com/science/article/pii/S1359431111001234> [Accessed 18 Nov. 2024].

Nanofluid Applications in Microchannel Heat Sinks. Available at: <https://www.sciencedirect.com/science/article/pii/S1359431111001234> [Accessed 18 Nov. 2024].

Hybrid Cooling Systems for High-Performance Electronics. Available at: <https://www.nature.com/articles/s41598-017-01916-6> [Accessed 18 Nov. 2024].

Thermal Management in Modern Automotive Design. Available at: <https://asmedigitalcollection.asme.org/thermalscienceapplication/article/10/3/031007/370282/Thermal-Management-of-Automotive-Li-Ion-Battery> [Accessed 18 Nov. 2024].

Advanced Materials for Heat Exchanger Fins. Available at: <https://www.materialstoday.com/composite-applications/features/advanced-materials-for-heat-exchangers/> [Accessed 18 Nov. 2024].

Deng, D. (2018). Additively Manufactured Inconel 718: Microstructures and Mechanical Properties. *Linköping Studies in Science and Technology*. Available at: <https://doi.org/10.3384/lic.diva-144491> [Accessed 18 Nov. 2024].

Sustainability Meets Durability: The Environmental Benefits of Stainless Steel. Available at: <https://www.alliagesunifies.com/blog/stainless-environmental-benefits> [Accessed 18 Nov. 2024].

Innovations in Processor Cooling Techniques Over Time. Available at: <https://pcsite.co.uk/innovations-in-processor-cooling-techniques-over-time/> [Accessed 18 Nov. 2024].

A Comprehensive Review of Methods of Heat Transfer Enhancement in Shell and Tube Heat Exchangers. *Journal of Thermal Analysis and Calorimetry*. Available at: <https://link.springer.com/article/10.1007/s10973-023-12265-3> [Accessed 18 Nov. 2024].

AMFG (2019) *3D printing for heat exchangers: application spotlight*. Available at: <https://amfg.ai/2019/07/17/3d-printing-for-heat-exchangers-application-spotlight/> (Accessed: 21 Nov 2024).

Cycle World (n.d.) *Motorcycle air-cooled engine fins explained*. Available at: <https://www.cycleworld.com/story/blogs/ask-kevin/motorcycle-air-cooled-engine-fins-explained/> (Accessed: 21 Nov 2024).

Advanced Thermal Solutions (ATS) (n.d.) *Tag: TEC*. Available at: <https://www.qats.com/cms/tag/tec/> (Accessed: 21 Nov 2024).

Motor Equipment News (n.d.) *High-performance radiators: high-performance engines – the honeycomb radiator, 120 years ago*. Available at: <https://motorequipmentnews.co.nz/article/high-performance-radiators-high-performance-engines-honeycomb-radiator-120-years-ago> (Accessed: 21 Nov 2024).

ScienceDirect (2017) *High-performance heat sinks and thermal management*. Available at: <https://www.sciencedirect.com/science/article/pii/S2214157X17300394#f0015> (Accessed: 21 Nov 2024).

Hardware Interviews (n.d.) *Describe a CPU heat sink geometry and why it has that geometry – what would you do to improve or decrease the heat transfer of a heat sink?*. Available at: <https://www.hardwareinterviews.fyi/t/describe-a-cpu-heat-sink-geometry-and-why-it-has-that-geometry-what-would-you-do-to-improve-or-decrease-the-heat-transfer-of-a-heat-sink/355/2> (Accessed: 21 Nov 2024).

Rapid 3D (n.d.) *Reinventing a high-performance CPU cooler with additive manufacturing*. Available at: <https://rapid3d.co.za/reinventing-a-high-performance-cpu-cooler-with-additive-manufacturing/> (Accessed: 21 Nov 2024).

Testing Autos (n.d.) *Car heating system*. Available at: https://www.testingautos.com/car_care/car-heating-system.html (Accessed: 21 Nov 2024).